

Safety Data Sheet

GRENZEN VERSCHIEBEN

according to Regulation (EC) No 1907/2006

Welding Torch - Coolant

Print date: 06.10.2014

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Welding Torch - Coolant

Product code:

40,0009,0046
40,0009,0075
40,0009,0077

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Coolant for corresponding Fronius - welding systems

1.3. Details of the supplier of the safety data sheet

Company name:	Fronius International GmbH	
Street:	Fronius Straße 5	
Place:	A-4642 Sattledt	
Telephone:	+43 / (0)7242 / 241-0	Telefax: +43 / (0)7242 / 241-8799
Internet:	www.fronius.com	
Responsible Department:	welding.techsupport@fronius.com	msds.techsupport@fronius.com
	Office hours: Mon – Thu: 08:00 – 16:30 Fri: 08:00 – 12:00	

1.4. Emergency telephone number:

+44 (0) 20 76 35 91 91

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

R phrases:
Flammable.

GHS classification

Hazard categories:
Flammable liquid: Flam. Liq. 3
Hazard Statements:
Flammable liquid and vapour.

2.2. Label elements

Signal word: Warning

Pictograms: GHS02



Hazard statements

H226 Flammable liquid and vapour.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



Safety Data Sheet

GRENZEN VERSCHIEBEN

according to Regulation (EC) No 1907/2006

Welding Torch - Coolant

Print date: 06.10.2014

Page 2 of 8

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P501 Dispose of contents/container to Dispose of waste according to applicable legislation.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Ethanol in aqueous solution

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
200-578-6	ethanol, ethyl alcohol	< 23 %
64-17-5	F - Highly flammable R11	
603-002-00-5	Flam. Liq. 2; H225	

Full text of R-, H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air.

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air. In case of fire: Formation of: Carbon dioxide (CO₂), Carbon monoxide.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Safety Data Sheet

GRENZEN VERSCHIEBEN

according to Regulation (EC) No 1907/2006

Welding Torch - Coolant

Print date: 06.10.2014

Page 3 of 8

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

No special measures are necessary.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharge. Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on storage compatibility

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

Coolant for corresponding Fronius - welding systems

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

8.2. Exposure controls



Protective and hygiene measures

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat or

**Safety Data Sheet****GRENZEN VERSCHIEBEN**

according to Regulation (EC) No 1907/2006

Welding Torch - Coolant

Print date: 06.10.2014

Page 4 of 8

drink.

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

By short-term hand contact:

Suitable material: Butyl caoutchouc (butyl rubber)

Thickness of the glove material: 0,5 mm

Breakthrough time (maximum wearing time): \geq 480 min.

By long-term hand contact

Suitable material: CR (polychloroprene, chloroprene rubber)

Thickness of the glove material: 0,5 mm

Breakthrough time (maximum wearing time): \geq 120 min.**Skin protection**

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	colourless
Odour:	like: Alcohol

Test method

pH-Value (at 20 °C): 7-8

Changes in the physical state

Melting point: not determined

Initial boiling point and boiling range: not determined

Flash point: 32 °C

Flammability

Solid: not applicable

Gas: not applicable

Lower explosion limits: 1,8 vol. %

Upper explosion limits: 15 vol. %

Auto-ignition temperature

Solid: not applicable

Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidizing.

Vapour pressure: not determined

Density (at 20 °C): 0,96 g/cm³

**Safety Data Sheet**

GRENZEN VERSCHIEBEN

according to Regulation (EC) No 1907/2006

Welding Torch - Coolant

Print date: 06.10.2014

Page 5 of 8

Water solubility: easily soluble

Solubility in other solvents

not determined

Partition coefficient: not determined

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

Flammable, Ignition hazard.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

Keep away from: Oxidising agent, Acid, Alkali (lye).

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

Acute toxicity

CAS No	Chemical name	Exposure routes	Method	Dose	Species	Source
64-17-5	ethanol, ethyl alcohol	oral	LD50	10470 mg/kg	Rat	OECD 401
		inhalative (4 h) vapour	LC50	117-125 mg/l	Rat	OECD 402

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

**Safety Data Sheet**

GRENZEN VERSCHIEBEN

according to Regulation (EC) No 1907/2006

Welding Torch - Coolant

Print date: 06.10.2014

Page 6 of 8

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1. Toxicity**

The product is not: Ecotoxic.

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h] [d]	Species	Source
64-17-5	ethanol, ethyl alcohol					
	Acute fish toxicity	LC50	14200 mg/l	96 h	Pimephales promelas (fathead minnow)	IUCLID
	Acute crustacea toxicity	EC50 mg/l	9268 - 14221	48 h	Daphnia magna	IUCLID

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
64-17-5	ethanol, ethyl alcohol				
	OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C	97 %	28	IUCLID	
	Readily biodegradable (according to OECD criteria).				

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol, ethyl alcohol	-0,31

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number:**

No dangerous good in sense of this transport regulation.

**Safety Data Sheet****GRENZEN VERSCHIEBEN**

according to Regulation (EC) No 1907/2006

Welding Torch - Coolant

Print date: 06.10.2014

Page 7 of 8

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.**14.4. Packing group:** No dangerous good in sense of this transport regulation.**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

1999/13/EC (VOC): < 23 %

Additional information

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC

National regulatory information

Employment restrictions: Observe employment restrictions for young people.

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Abbreviations and acronyms**ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant R-phrases (Number and full text)

11 Highly flammable.

Relevant H- and EUH-phrases (Number and full text)

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.



Safety Data Sheet

GRENZEN VERSCHIEBEN

according to Regulation (EC) No 1907/2006

Welding Torch - Coolant

Print date: 06.10.2014

Page 8 of 8

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)