

WIRE WOUND POWER INDUCTOR, SHIELDED OFFERINGS (CSMxxxxx SERIES)

Part Number: CSM0310D-1R0N

CSMxxxxx-###t: xxx= code in table 0310D | ###=inductance code 1R0 | t= tolerance in table (N)

		0310D	0315D	0418D	0840D
R90	0.9μH				0840D (N)
1R0	1.0μH	0310D (N)	0315D (N, M)	0418D (N)	
1R2	1.2μH	0310D (N)			
1R4	1.4μH				0840D (N)
1R5	1.5μH	0310D (N)	0315D (N, M)	0418D (N)	
1R8	1.8μH		0315D (N, M)		
2R0	2.0μH				0840D (N)
2R2	2.2μH	0310D (N, M)	0315D (N, M)	0418D (N, M)	0840D (N)
2R7	2.7μH	0310D (N, M)	0315D (N, M)		
3R3	3.3μH	0310D (N, M)	0315D (N, M)	0418D (N, M)	0840D (N)
3R6	3.6μH	0310D (N, M)	0315D (N, M)		0840D (N)
4R7	4.7μH	0310D (N, M)	0315D (N, M)	0418D (N, M)	0840D (N)
5R6	5.6μH	0310D (N, M)	0315D (N, M)		
6R2	6.2μH		0315D (N, M)		
6R8	6.8μH	0310D (N, M)	0315D (N, M)	0418D (N, M)	0840D (N)
100	10μH	0310D (N, M)	0315D (N, M)	0418D (N, M)	0840D (M)
120	12μH		0315D (N, M)		
150	15μH	0310D (N, M)	0315D (N, M)	0418D (N, M)	0840D (M)
180	18μH	0310D (N, M)	0315D (N, M)		
220	22μH	0310D (N, M)	0315D (N, M)	0418D (N, M)	0840D (M)
270	27μH	0310D (N, M)			
330	33μH	0310D (N, M)	0315D (N, M)	0418D (N, M)	0840D (M)
390	39μH	0310D (N, M)	0315D (N, M)		
430	43μH		0315D (N, M)		
470	47μH	0310D (N, M)	0315D (N, M)	0418D (N, M)	0840D (M)
560	56μH		0315D (N, M)		
680	68μH		0315D (N, M)	0418D (N, M)	0840D (M)
101	100μH		0315D (N, M)	0418D (N, M)	0840D (M)
151	150μH			0418D (N, M)	
221	220μH			0418D (N, M)	