

WIRE WOUND POWER INDUCTOR, HIGH CURRENT, SHIELDED OFFERINGS (MCSxxxx SERIES)

Part Number: MCS0420-R47M

MCSxxxx-###t: xxx= code in table 0420 | ###=inductance code R47 | t= tolerance in table (M)

		0420	0630	1040
R22	0.22μH		0630 (M)	1040 (M)
R33	0.33μH		0630 (M)	
R36	0.36μH			1040 (M)
R47	0.47μH	0420 (M)	0630 (M)	1040 (M)
R56	0.56μH		0630 (M)	1040 (M)
R68	0.68μH		0630 (M)	1040 (M)
R82	0.82μH		0630 (M)	
1R0	1.0μH	0420 (M)	0630 (M)	1040 (M)
1R5	1.5μH	0420 (M)	0630 (M)	1040 (M)
2R2	2.2μH	0420 (M)	0630 (M)	1040 (M)
3R3	3.3μH	0420 (M)	0630 (M)	1040 (M)
4R7	4.7μH	0420 (M)	0630 (M)	1040 (M)
6R8	6.8μH	0420 (M)	0630 (M)	1040 (M)
8R2	8.2μH		0630 (M)	
100	10μH		0630 (M)	1040 (M)
150	15μH		0630 (M)	1040 (M)
220	22μH		0630 (M)	1040 (M)
330	33μH			1040 (M)
470	47μH			1040 (M)