



Solutions

HVAC systems

HVAC systems

Solutions for



Air handling units

Heat pumps

Chillers

Roof tops

Pellet burners

ABOUT CARLO GAVAZZI

Carlo Gavazzi Automation is an international group active in the design, manufacture and marketing of electronic equipment targeted at the global markets of industrial and building automation.

Our history is full of firsts and our products are installed in a huge number of applications all over the world. With more than 80 years of successful operation, our experience is unparalleled.

We have our headquarters in Europe and numerous offices around the world.

Our R&D competence centres and production sites are located in Denmark, Italy, Lithuania, Malta and the People's Republic of China.


We operate worldwide through 22 of our own sales companies and also selected representatives in more than 65 countries, from the United States in the West to the Pacific Rim in the East.

Our core competence in automation spans four product lines: Sensors, Switches, Controls and Fieldbuses.

Our wide array of products includes sensors, monitoring relays, timers, energy management system, solid state relays, safety devices and fieldbus systems.

We focus our expertise on offering state-of-the-art product solutions in selected market segments.

Our customers include original equipment manufacturers of packaging machines, plastic-injection moulding machines, food and beverage production machines, conveying and material handling equipment, door and entrance control systems, lifts and escalators, as well as heating, ventilation and air-conditioning devices.



DESIGNED TO MEET MARKET REQUIREMENTS

It is becoming more and more important to have an energy-efficient integrated HVAC system for buildings. That is why HVAC components, such as heat pumps, rooftops, chillers and air handling units need more effective control and additional functions so as to improve overall performance. Communication is important, both for the building management system, using protocols such as BACnet, and for the individual units, where Modbus implementation is becoming more and more common, involving components such as the main controller, the compressor, the expansion valve, the energy meter and the soft starter.

Enhance performance with our monitoring relay solutions

- Various monitoring functions: phase sequence, phase loss and voltage level
- Compact dimensions
- Worldwide approvals

Increase system efficiency with our solutions for energy management

- Energy meters & power transducers
- Power analysers
- Current transformers
- Serial communications
- Solutions with BACnet communication
- Web-server solutions

Extend the lifetime of scroll compressors with easy to use soft starting solutions

- Dedicated solutions for scroll compressors
- 1- and 3-phase compact solutions
- 2- and 3-phase controlled solutions
- Integrated monitoring functions
- Modbus communication

Resistive heaters switching with solid state relays

- ON/OFF solid-state contactors
- Proportional controllers
- Wide range of 1-phase and 3-phase solutions
- Modular solutions

HVAC systems

Air handling units



Energy analysers

EM340

Soft starters

RSGD

Solid state relays

**RGC3P/RGC2P
RGC1P/RGS1P
RM1E**

Energy/power transducers

**CPT-DIN
ET340**

Monitoring relays

**DPD
DWA01
DPB01/DPB51**

Solid state relays

**RG
RM
RK**

Carlo Gavazzi's comprehensive range of energy meters, energy analysers and power transducers keep your plant monitored 24/7.

The following communication protocols are available: Modbus, BACnet, M-bus and Profibus.

Our web server solutions also provide multi-site monitoring.

Our easy to use and reliable soft starter range, with extended ramp-up times, ensures smoother centrifugal fan starts. An intelligent algorithm for current reduction and current balancing results in fewer electrical disturbances and less vibrations during starts.

A wide selection of solid-state relays offers analogue switching versions for

the efficient control of resistor packs for heating or dehumidification and Zero Cross switching to reduce electrical spikes on the network.

Our compact monitoring relays for power factor monitoring allow the detection of broken belts in centrifugal fans.

- Efficiency improvement
- Easy access to monitored data via IT network
- Reduced maintenance and lower mechanical noise when fan starts
- Fewer electrical disturbances and lower current peaks
- Reduced air pressure shocks in the case of canvas ducts
- Optimal de-humidification



Heat pumps



Soft starters

**RSBS/RSBD
RSBS HP
RSBT**

Solid state relays

**RG
RM
RGC3P**

Monitoring relays

DPA51

Energy meters/analysers

**EM110
EM111
EM340**

Timers

**DAA51
DMB51**

Electromechanical relays

RMIA

Carlo Gavazzi's comprehensive range of solid state relays for auxiliary heater switching also includes low noise versions so as to reduce disturbance to the supply network.

Slim energy meters are available for 1-phase applications.

Our wide range of monitoring relays provides phase loss, phase sequence, over and under-voltage monitoring.

The complete range for fixed speed scroll compressors consists of single and three phase dedicated to soft starters and two and three-phase controlled solutions with a patented self-learning algorithm to limit scroll compressor start current. The RSBS and RSBT soft starters are compliant with EMC Class B (residential).

- Noise-free switching of auxiliary heaters
- Plug'n'play soft starting solutions
- Best-in class current reduction
- Compliant with the stringent requirements for noise emissions
- Easy to fit in electrical panels
- More protection for the compressor
- Quick detection of abnormal conditions



HVAC systems

Chillers



Monitoring relays

DPB51/DPB01
DPA51/DPA53
DLA71/DPD

Switching power supplies

SPDC/SPDM
SPM/SPPC

Soft starters

RSBD/RSWT
RSBT/RSGD

Power quality analysers

WM20
WM40
WM30

Energy analysers

EM210
EM340

Energy/power transducers

ET340
CPT

Timers

DAA51
DAC51

Carlo Gavazzi's compact and cost-effective range of power supplies, timers for star/delta switching and monitoring relays are designed to meet your toughest specification requirements for panel mounting. Two-phase controlled solutions with current balancing, three-phase scroll compressor soft starters up to 95 A with a dedicated algorithm for multi-scroll compressor applications. Our solutions for energy management for DIN and panel mount are comprehensive and versatile for the monitoring and power analysis. Modbus or BACnet communication ports are available for communication with controllers and BMS.

- Easy installation even in limited space
- Protection of compressors
- Reduction of starting current by 50%
- No settings required
- Improved efficiency
- Remote access to data
- Easy integration into existing communication networks



Roof tops



Monitoring relays

**DPD
DPA51
DPB01/51**

Switching power supplies

**SPM
SPDC/SPDM
SPPC**

Soft starters

**RSBT
RSWT
RSBD**

Power quality analysers

**WM40
WM30
WM20**

Energy meters/analysers

EM24

Solid state relays

**RGC3P
RGC3A
RGC1P**

Timers

**DAA51
DAC51**

Carlo Gavazzi's range of energy meters and power analysers fulfil all requirements in terms of both features and costs, for remote monitoring of energy consumption.

The comprehensive communication protocols and web-server solutions allow flexible and easy integration.

We offer proportional controllers for heaters and fans. Our compact IP20 solutions with phase angle control for fan speed regulation (one-phase and three-phase), also two-phase solutions for resistive heater modulation (RGC2P) full cycle switching.

Our range of soft starters are able to provide integrated diagnostic functions for additional protection.

The related operational temperature range is up to 60°C.

The self-learning algorithm, which is active at every compressor start, ensures that the compressor always starts with the correct parameters.

Modbus communication is also available to transmit real-time data to the machine controller.

- Efficiency improvement
- Easy data transmission to the BMS or the controller
- Automatic settings
- Reliable operation even at high temperatures
- Compact and cost-effective solutions



HVAC systems

Pellet burners



Inductive proximity sensors

ICB12

Capacitive sensors

**CA30CA
CD50
CA18**

Solid state relays

**RM1A
RP1**

Carlo Gavazzi's compact and cost-effective series of solid state relays is widely known for its reliability and robustness for high switching frequencies of water pump or smoke fan.

Our ICB inductive sensors are used to detect the position of the dampers so as to direct the air flow where needed. Short circuit, reverse polarity and transients protection is assured.

Our new 4th generation of Tripleshield sensors CA30CA.. allows a dust alarm to be sent when the sensor gets dirty and needs to be cleaned.

A temperature alarm is sent when the temperature exceeds 60°C.

EMC immunity and high sensing

capability ensure correct detection in all conditions, especially where pellet-dust remains on the reservoir surface.

- High switching frequency
- Silent and reliable operation even in harsh environments
- Safer operation of the burner
- Intelligent alarms
- Different configurations available, tailored to specific needs



Our expertise in scroll compressors



Soft starters

**RSBS
RSBS HP**

Monitoring relays

DPA51

Soft starters

**RSBD
RSBT**

In a heat pump, as well as in a rooftop or in a chiller unit, the compressor is the heart of the system. It supplies the inverse cycle and is also the most expensive and energy-consuming device in the machine. When starting, the scroll compressor operates in a very abrupt way and this can lead to undesirable effects to the machine itself and to the nearby environment. A direct on-line (DOL) start is performed in just 3 cycles (around 60 ms) for a three-phase machine and a little more for 1-phase ones. This can result in rapid inrush current (around 8 times the nominal current) and significant vibrations. The first effect of high inrush current is voltage fluctuations during starts, especially where the grid is not so resistant, as in many domestic or commercial

environments or in locations far from the energy source. This leads to lights flickering and potential interference with equipment such as LAN networks, Wifi, smartphones and tablets. The second effect is that the nominal current for the utility contract may be exceeded, which could result in fines from the energy supplier or having to increase the contract power at a higher cost. In addition, direct on-line starts cause wear and tear to the coils, reducing the lifetime of the compressor. Vibrations mainly cause a shock to the motor, starting from the shaft, which means shorter compressor lifetime. They also lead to mechanical shock to the pipes which, especially in the long term and for larger machines, can cause refrigerant leakage. Last but not least, the noise of a

direct on-line start can be rather annoying. These problems can be solved by using our range of soft starters specifically designed for scroll compressor applications. Inrush current is reduced by 50 to 55% and the compressor is started within 1s, allowing a smooth start and proper compression and lubrication. The three-phase RSBD and RSBT soft starters are provided with an auto-adaptive algorithm which ensures the best inrush current reduction at every start. As the soft starter follows the changes in the compressor and the system over time, no setting is needed. At the same time, when unexpected conditions occur, such as a very high pressure difference in the refrigeration circuit, the soft starter will react ensuring starting even in the worst conditions.

HVAC systems

Our product range

3-phase scroll compressor soft starters



RSBT

- Enhanced current reduction capability with patented auto-adaptive algorithm
- Integrated advanced diagnostic functions
- 3-phase controlled and internally bypassed
- Compliant with Residential (Class B) Limits for Emissions
- cULus listed, VDE (EN60335-2-40)

MAIN FEATURES

- Plug&Play: no external settings needed
- Typically >50% scroll compressor inrush current reduction
- Compact dimensions: better panel space savings

3-phase scroll compressor soft starters



RSBD 45 mm

- Current balancing algorithm to reduce unbalance on uncontrolled phase
- Patented auto-adaptive algorithm for better inrush current reduction
- 2-phase controlled and internally bypassed
- Alarm and top of ramp indication
- cULus - CCC approved

MAIN FEATURES

- Plug&Play: no external settings needed
- Operational current: 12 AAC up to 45 AAC @ 40°C
- Multi-voltage operation: 220-400 VAC

3-phase scroll compressor soft starters



RSBD 75 mm

- Self-learning algorithm for current reduction and current balancing
- Operational current: 55/70/95 AAC
- Operational voltage: 220 - 600 VAC, 50/60 Hz
- Alarm, Top of ramp and Run relay output
- cULus approved

MAIN FEATURES

- Compact dimensions: 95 A in 75 mm wide housing
- Plug and play: no user settings required
- Internally Bypassed

3-phase centrifugal pump soft starters



RSWT 45/75/120 mm

- Motor rating: up to 45 kW (90 AAC)
- 3-phase controlled & internally bypassed
- Ramp-up/Ramp-down time: up to 20sec
- "Operational voltage: RSWT40: 220 - 400 VAC, RSWT60: 220 - 600VAC"
- PTC input, Alarm - Top of Ramp - Run relay indication

MAIN FEATURES

- Easy to use and setup
- Self-learning algorithm to improve pump starts/stops
- Integrated overload protection (Class 10)

3-phase scroll compressor soft starters



RSBT 120 mm

- Patented algorithm achieves 50% current reduction vs direct on line start
- Operational current: 55/70/95 AAC
- Operational voltage: 220 - 480 VAC, 50/60 Hz
- Alarm, Top of ramp relay output
- cULus approved

MAIN FEATURES

- Compact dimensions: 95 A in 75 mm wide housing
- Plug and play: no user settings required
- 3-phase controlled with internal bypass
- Modbus RTU over RS485 serial communication

1-phase scroll compressor soft starters



RSBS / RSBS HP

- Current limit starting
- Advanced diagnostic functions
- Internally bypassed
- Up to 12 starts per hour
- cULus listed - EN60335-2-40 approval

MAIN FEATURES

- Plug&Play: no external settings needed
- Space saving IP20 design
- Integrated starting capacitor
- Optimised algorithm for high pressure starts (RSBS HP)

Our product range

Compact motor soft starters



RSGD 45 / 75 mm

- Operational voltage range: 187-440 VAC, 187-660 VAC
- Operational current range: 12 AAC up to 100 AAC
- Control voltage: 24 VAC/DC, 110-400 VAC
- Auxiliary relays for top of ramp and alarms
- cULus - CCC approved

MAIN FEATURES

- Compact dimensions: up to 22 kW in 45 mm wide housing (RSGD 45 mm), up to 55 kW in 75 mm wide housing (RSGD 75 mm)
- Easy to setup: self-learning algorithm
- Internally bypassed and supplied

Phase sequence and loss relays



DPA51 / DPA53

- Dimensions: 81 x 17.5 x 67.2 mm DIN rail housing
- Phase sequence and loss relay
- 3 phase AC (own power supply); regenerated voltage
- Power supply 208-480 VAC ($\pm 15\%$)
- Undervoltage detection
- UL - CSA - CCC approved

MAIN FEATURES

- Compressor protection from reverse running and phase loss
- 17.5 mm width: the smallest in the market
- Plug&Play: no settings needed

Phase relays under/over voltage



DPB01 / DPB51 / DPB71

- Dimensions 81 x 17.5 or 35.5 (DPB71) x 67.2 mm DIN-rail housing
- TRMS 3-Phase sequence, Phase and Neutral loss relay
- 3 phase independent over and under voltage with adjustable delay
- Star and Delta power supply from 208-480 VAC ($\pm 15\%$)
- UL - CSA - CCC approved

MAIN FEATURES

- Compressors protection from reverse running and phase loss
- Detects L-L and L-N voltage
- 17.5 mm width: the smallest in the market
- Independent voltage setpoints and built-in delays

Cosφ relays



DWA01

- Dimensions 83 x 22.5 x 99.5 mm DIN rail housing
- Cosφ monitoring relays
- 3 phase AC (own power supply); regenerated voltage
- Power supply 208-240 VAC or 380-480 VAC
- UL - CSA approved

MAIN FEATURES

- Detects any potentially dangerous change of the cosφ
- Direct current connection or by CT
- Easy setup

Pump alternating relays



DLA71

- Dimensions: 81 x 35.5 x 67.2 mm DIN rail housing
- Pump alternating relay for 2 or 3 pumps
- Galvanically separated power supply, 24/48 or 115/230 VAC
- 2x or 3x 5A SPST relay output
- UL - CSA approved

MAIN FEATURES

- Built-in function for automatic rotation of the pumps
- Built-in delay for the second or third pump in case simultaneous activation is required
- Plug and play: no settings needed

3-phase monitoring relays



DPD

- Dimensions: 22.5mm DIN rail mounting Enclosure
- 120 VAC to 480 VAC Delta & Star mains
- Voltage and frequency monitoring
- 2 SPDT 8 A relay outputs
- UL - CSA - CCC approved

MAIN FEATURES

- NFC programming
- Up to 10 configurable setpoints
- Apps for Android and Windows PC programming

HVAC systems

Our product range

PCB mounted solid state relays



RP1

- Dimensions: 37 x 43 x 22 mm, PCB mounted
- Rated operational voltage: up to 480 VAC
- Rated operational current: up to 10 AAC
- Control input range: 4-32 VDC
- CE - cURus approved

MAIN FEATURES

- Zero cross or instant-on switching
- Optional DIN mounting with RP..Mx accessory

1-phase solid state relays



RGS1A / RGC1A

- Product width 17.5 mm up to 70 mm, DIN or panel mounting
- Ratings: up to 660 VAC, 90 AAC, 18000 A²s
- Integrated output overvoltage protection
- Control input: 4-32 VDC, 20-275 VAC (24-190 VDC)
- CE - cULus (RGC) - UR (RGS) - CSA (RGS) - VDE - GL (up to 30 AAC)

MAIN FEATURES

- Integrated heatsink (RGC1A) or without heatsink (RGS1A)
- 100 kA short circuit current rating
- Optional overtemperature protection (RGC1A)

1-phase proportional controllers



RGS1P / RGC1P

- Product width 35 mm up to 70 mm, DIN or panel mounting
- Ratings: up to 660 VAC, 90 AAC, 18000 A²s
- Control input: 4-20 mA, 0-10 VDC, 0-5 VDC, 1-5 VDC, external potentiometer
- LED indication for control and load status
- CE - cULus (RGC), cURus (RGS), CSA (RGS) approved

MAIN FEATURES

- Power control via a selectable switching mode (phase angle, full cycle, advance full cycle or soft start switching)
- Compact dimensions
- Reliability with integrated overvoltage protection

1-phase solid state relays



RM1A / RAM1A

- Dimensions: 58.2 x 44.8 x 28.8 mm, panel mount
- Rated operational voltage: up to 660 VAC
- Rated current: 25 AAC, 50 AAC, 75 AAC, 100 AAC, 125 AAC
- Control input: 4-32 VDC, 20-280 VAC
- CE - cURus - CSA - VDE (RAM) - CCC approved

MAIN FEATURES

- Zero cross or Random switching
- Suited for resistive, inductive or capacitive loads
- Integrated output overvoltage protection (RM1)

1-phase proportional controllers



RM1E

- Dimensions: 58.2 x 44.8 x 28.8 mm, panel mount
- Rated operational voltage: up to 660 VAC
- Rated current: 25 AAC, 50 AAC, 100 AAC
- Control input: 4-20 mA, 0-10 V
- CE - cURus - CSA approved

MAIN FEATURES

- Phase angle switching
- Integrated overvoltage protection
- 0 to 99% power output control

2-pole solid state relays



RK

- Dimensions: 45 x 58 x 33 (44) mm, panel mount
- Independent control (RKD2..) or common control (RK2..)
- Ratings : up to 660 VAC, 50 AAC /pole, 75 AAC /pole
- Control input: 4-32 VDC
- CE - cURus - CSA - VDE approved

MAIN FEATURES

- Integrated output overvoltage protection
- Pre-attached thermal pad
- Conformant to EN 60335-1

Our product range

3-phase solid state contactors	3-phase proportional controllers	Timers
---	---	---------------



RGC2A / RGC3A

- Product width 54 mm up to 70 mm, DIN mount
- Rated operational voltage: up to 660 VAC
- Rated current: up to 75 AAC/pole (RGC2A), 65 AAC/pole (RGC3A) @ 40°C
- Control input: 5-32 VDC, 20-275 VAC (24-190 VDC)
- CE - cULus

MAIN FEATURES

- Integrated output overvoltage protection
- Optional monitoring for SSR and load circuit malfunction (RGC..M)
- 100 kA short circuit current rating



RGC2P / RGC3P

- Product width 54 mm up to 70 mm, DIN mount
- Rated operational voltage: 180 - 660 VAC
- Rated current: up to 75 AAC/pole (RGC2P), 65 AAC/pole (RGC3P) @ 40°C
- Control input: 0-20 mA, 4-20 mA, 12-20 mA, 0-10 V, 0-5 V, 1-5 V, external potentiometer
- CE - cULus

MAIN FEATURES

- Integrated output overvoltage protection
- Phase angle, Distributed full cycle or Soft start as switching modes
- Integrated monitoring for SSR and load circuit malfunction



DAA51 / DAC51

- Dimensions: 81 x 17.5 x 67.2 mm DIN rail housing
- Delay on operating function (DAA), start/delta function (DAC)
- Universal power supply
- Repeatability: < 0.2%
- UL - CSA approved

MAIN FEATURES

- Extended delay-on-operating time, selectable from 0.1 s to 100 h
- Star-delta control function with star and star-to-delta adjustable times
- Protection against frequent compressor starting and from big inrush currents

Timers	Electromechanical relays	Electromechanical relays
---------------	-------------------------------------	-------------------------------------



DMB51

- Dimensions: 81 x 17.5 x 67.2 mm DIN rail housing
- Combined AC and DC power supply
- Repeatability: < 0.2%
- UL - CSA - RINA approved

MAIN FEATURES

- Delay on operate/release-, interval (manual/automatic start)
- Double interval; symmetrical recycler (ON or OFF first)
- Timing range from 0.1 s to 100 h



RMIA series

- 2 x 10 A and 4 x 5 A versions
- DC coils: 6-220 V
- AC coils: 6-380 V
- Free wheeling diode integrated
- Sockets for PCB or DIN rail installations

MAIN FEATURES

- Contacts suitable for High Inrush loads
- Very compact size
- LED, latchable mechanical push button and flag as standard



RCP series

- 2 x 10 A and 3 x 10 A contacts
- Industry standard relay
- High immunity to supply voltage fluctuation
- DC coils: 6-110 V
- AC coils: 6-230 V

MAIN FEATURES

- Octal and Undecal
- LED, latchable mechanical push button and flag as standard
- Wide selection of sockets for PCB and DIN rail

HVAC systems

Our product range

AC Current transformers



E83

- Dimensions: 56 x 22.5 x 49 mm
- 7 input ranges
- Output 4-20 mA DC
- No power supply
- UL - CSA approved

MAIN FEATURES

- Easy interface to PLC
- Built in hall sensor for current sensing
- LED indication

Power transducers



CPT-DIN

- Dimensions: 83.5 x 45 x 98.5 mm DIN rail housing
- Accuracy 0.5 % (voltage, current)
- Measurement by CT and VT
- Front protection degree IP20
- Analogue, digital, pulse or serial outputs available

MAIN FEATURES

- Very compact size power transducer
- Provides electrical variables set to a PLC to manage compressors and other loads
- Suitable for on-board panel installation

3-phase energy transducers



ET340

- Dimensions: 3 DIN module; DIN-rail mounting
- Measurement of voltage, current, power, power factor, frequency, THD (V, A)
- Bi-directional energy metering, 2 tariffs, cl. 1 (EN62053-1)
- Measuring inputs: 208 to 400 V_{LL} AC, 65 A

MAIN FEATURES

- Self-powered
- RS485 Modbus port (screw, 2x RJ45)
- Optical port
- Sealable terminal covers
- CE approved

1-phase energy meters /analysers



EM110 / EM111

- Dimensions: 1 DIN module; DIN-rail mounting
- Electromechanical totalizer (EM110) or backlit touch LCD (EM111)
- Measurement of voltage, current, power, power factor and frequency (EM111)
- Bi-directional energy metering, 7 digits, cl. B (EN50470)
- Measuring inputs: 115/230 VAC, 45 A

MAIN FEATURES

- Self-powered
- Pulse output or as an alternative: RS485 Modbus, M-Bus (EM111)
- Sealable terminal covers
- CE, MID (PFA (EM111) and PFB) approved

3-phase energy analysers



EM210

- Dimensions: 4 DIN modules or 72 x 72 mm
- Installation: DIN-rail or panel mounting in a single product
- 3-phase energy meters with CT/VT connection
- Measurement of voltage, current, power, power factor and frequency
- Pulse output
- RS485 Modbus RTU, high speed (up to 115kbps)

MAIN FEATURES

- Self-powered
- Sealable terminal covers
- Very compact housing to save space
- CE, cULus, MID approved

3-phase energy meters/analysers



EM24 DIN

- Dimensions: 4 DIN modules, DIN-rail mounting
- Meter for energy from CT 5 A or for direct energy 65 A
- Measurement of voltage, current, power, power factor and frequency.
- Bi-directional energy metering on 2 8-digit counters, cl. B (EN50470-3)
- Inputs: 3x230(400)VAC, 5 A, 65 A

MAIN FEATURES

- 115-230 VAC power supply or self-powered
- 3 inputs for external dimension counting (IS)
- Pulse or relay output: RS485 Modbus RTU, M-Bus
- Sealable terminal covers
- CE, MID (PF), cULus (5A version) approved

Our product range

3-phase energy analysers



EM340

- Dimensions: 3 DIN modules; DIN-rail mounting
- Backlit touch LCD
- Measurement of voltage, current, power, power factor and frequency
- Bi-directional energy metering on 2 8-digit counters, cl. B (EN50470)
- Measuring inputs: 3 x 230 (400) VAC, 65 A

MAIN FEATURES

- Self-powered
- Pulse output or as an alternative: RS485 Modbus, M-Bus
- Sealable terminal covers
- CE, MID (PFA and PFB) approved

3-phase power analysers



WM20

- Dimensions: 96 x 96 mm panel mounting housing
- Accuracy 0.2 % (voltage, current)
- Universal power supply
- Front protection degree IP65, NEMA4X, NEMA12
- cULus approved

MAIN FEATURES

- Provides installation data to a SCADA to manage the whole system
- Modular housing to build the instrument according to the real application needs
- Modbus and BACnet (both RS485 or Ethernet) and Profibus DPVO communication ports available

3-phase power quality analysers



WM30 / WM40

- Dimensions: 96 x 96 mm panel mounting housing
- Accuracy 0.2 % (voltage, current)
- Universal power supply
- Front protection degree IP65, NEMA4X, NEMA12
- cULus approved - Solar California listed

MAIN FEATURES

- 16-alarm PLC logic and digital inputs for utility metering (WM40)
- Modular housing to build the instrument according to the real application needs
- Modbus and BACnet (both RS485 or Ethernet), Profibus DPVO and Ethernet/IP communication ports available
- Built-in datalogger for instantaneous variables, dmd profiles and events (WM40)

Capacitive sensors



CA18

- Dimensions: M18 / M30
- Tripleshield™ sensor protection
- Plastic housing, DC and AC versions
- Sensing distance 0.5-12 mm
- CE - UL - CSA approved

MAIN FEATURES

- Optimised features for level detection in plastic and rubber applications
- Sensing face can withstand temperatures up to 120°C
- Protection: short circuit, transient and reverse polarity

Capacitive sensors



CA30

- 4-12 mm sensing distance adjustable
- Time delay on operate or release, up to 10 minutes adjustable
- Multi voltage supply: 20.4-255 VAC/DC
- 2 A, SPDT relay output
- Housing M30 x 100 mm
- CE - cULus approved

MAIN FEATURES

- Level sensor for solid, fluid or granulated substances
- IP67, NEMA 1, 2, 4, 4X, 5, 6, 6P, 12

Capacitive sensors



CA30CA.. series

- High EMC Immunity.
- M30 mm housing, easy to mount
- Power supply 10-40 VDC, 200 mA NPN or PNP, NO and NC
- CE - UL - CSA approved

MAIN FEATURES

- Reliable detection of pellets in the burner's feeding system
- Dust alarm output
- Temperature alarm output at 60°C

HVAC systems

Our product range

Capacitive sensors



CD50

- Dimensions: 50 x 30 x 7 mm
- Flat pack sensor, easy to mount
- Power supply 10-30 VDC, 50 mA NPN or PNP, NO or NC
- CE approved

MAIN FEATURES

- Detection of condensed water from Airconditioning system

Conductive level systems



CLD / CLP

- Exact level detecting with insulated electrodes
- SPDT 8 A relay output
- 24-240 AC/DC or 230 AC or 115 AC
- CE - UL - CSA approved

MAIN FEATURES

- Detection of condensed water from air conditioning system
- Easy to install with simple electrodes
- Wide sensitivity 250 Ω to 500 k Ω

Conductive level probes



CLH

- 3-5 stainless steel electrodes
- User defined electrode length
- Insulation available in Kynar or Polyolefine
- 1 1/2" pipe thread mounting
- IP65/68 rating

MAIN FEATURES

- -20°C to 90°C
- Replaceable electrodes
- Extendable electrodes

Inductive proximity sensors



ICB12 / ICB18

- M12 and M18 NPB housing in short or long barrel lengths
- Sensing distance from 2 mm up to 20 mm
- Output functions: NO or NC, NPN or PNP
- Two meter oil resistant PVC cable or M12 plug version
- CE - cULus - cCSAus approved

MAIN FEATURES

- High precision and reliability thanks to the microprocessor technology
- Eco-friendly potting material
- Short-circuit and overload LED indication
- Laser engraved on front cap, permanently legible

Photoelectric level sensors



VP / VPA / VPB

- 3/8" pipe thread x 70.5 (74 mm) housing
- Power supply 10-40 VDC, 200 mA NPN or PNP, NO and NC
- CE approved

MAIN FEATURES

- Detection of condensed water from Air-conditioning system
- Reliable detecting of water even with oil presence

DIN rail power supplies



SPD

- DIN rail housing
- 1-phase (5-480 W), 2-phase (100 W), 3-phase (120-960 W)
- Rated input voltage: 85-264 VAC (1-phase), 380-575 VAC (2-phase), 340-575 VAC / 480-820 VDC (3-phase)
- UL - cUL listed - TÜV/CE approved

MAIN FEATURES

- Power Factor Correction (PFC)
- Parallel versions available
- High efficiency (up to 93%)

Our product range

DIN rail power supplies



SPDM 120W

- 24 VDC, 120 W Output
- Efficiency up to 88%
- Ultra-slim dimension: 45mm width
- Universal input voltage AC and DC
- Operating temperature from -25° to +70° C
- Stainless steel enclosure

MAIN FEATURES

- Output protections: OVP/OLP/SCP/OTP
- DC OK LED indication
- Built-in current limiting circuit

DIN rail compact power supplies



SPDC 120W

- 12 or 24 VDC, 120 W Output
- 32 mm width, high compactness
- Very high efficiency up to 91%
- Operating temperature from -25° to +70° C
- Universal input 90 VAC ~ 264 VAC / 127 VDC ~ 370 VDC

MAIN FEATURES

- DC OK relay output and LED indication
- PFC
- Parallel connection selection switch

DIN rail compact power supplies



SPDC 240W

- 24 VDC, 240 W output
- 45 mm width, high compactness
- Very high efficiency up to 94%
- Operating temperature from -25° to +70° C
- Universal input 90 VAC ~ 264 VAC / 127 VDC ~ 370 VDC

MAIN FEATURES

- DC OK relay output and LED indication
- PFC > 0.95
- Parallel connection selection switch

Low profile DIN power supplies



SPM

- DIN rail housing
- Universal input 90-264 VAC / 120-370 VDC
- Single phase and battery charger versions available
- UL - cUL listed - TÜV/CE approved

MAIN FEATURES

- Operating temperature w/o derating -25°C to +60°C
- Short circuit and Overload protection
- High efficiency (up to 89%)

Enclosed power supplies



SPPC

- Universal Input 115 / 230Vac
- Output Voltages: 5V, 12V, 24V and 48V
- Output powers from 25 to 800W
- Wide temp range from -25°C to +70°C (-13°F to 158°F)
- cURus and CE approved

MAIN FEATURES

- Fully protected output: OVP, SCP
- Very compact dimension
- PFC versions available from >75W



OUR SALES NETWORK IN EUROPE

AUSTRIA

Carlo Gavazzi GmbH
Ketzergrasse 374,
A-1230 Wien
Tel: +43 1 888 4112
Fax: +43 1 889 10 53
office@carlogavazzi.at

FRANCE

Carlo Gavazzi Sarl
Zac de Paris Nord II, 69, rue de la Belle Etoile,
F-95956 Roissy CDG Cedex
Tel: +33 1 49 38 98 60
Fax: +33 1 48 63 27 43
french.team@carlogavazzi.fr

ITALY

Carlo Gavazzi SpA
Via Milano 13,
I-20020 Lainate
Tel: +39 02 931 761
Fax: +39 02 931 763 01
info@gavazziacbu.it

SPAIN

Carlo Gavazzi SA
Avda. Iparragirre, 80-82,
E-48940 Leioa (Bizkaia)
Tel: +34 94 480 4037
Fax: +34 94 431 6081
gavazzi@gavazzi.es

BELGIUM

Carlo Gavazzi NV/SA
Mechelsesteenweg 311,
B-1800 Vilvoorde
Tel: +32 2 257 4120
Fax: +32 2 257 41 25
sales@carlogavazzi.be

GERMANY

Carlo Gavazzi GmbH
Pfnorstr. 10-14
D-64293 Darmstadt
Tel: +49 6151 81000
Fax: +49 6151 81 00 40
info@gavazzi.de

NETHERLANDS

Carlo Gavazzi BV
Wijkermeerweg 23,
NL-1948 NT Beverwijk
Tel: +31 251 22 9345
Fax: +31 251 22 60 55
info@carlogavazzi.nl

SWEDEN

Carlo Gavazzi AB
V:a Kyrkogatan 1,
S-652 24 Karlstad
Tel: +46 54 85 1125
Fax: +46 54 85 11 77
info@carlogavazzi.se

DENMARK

Carlo Gavazzi Handel A/S
Over Hadstenvej 40,
DK-8370 Hadsten
Tel: +45 89 60 6100
Fax: +45 86 98 15 30
handel@gavazzi.dk

GREAT BRITAIN

Carlo Gavazzi UK Ltd
4.4 Frimley Business Park,
Frimley, Camberley, Surrey GU16 7SG
Tel: +44 1 276 854 110
Fax: +44 1 276 682 140
sales@carlogavazzi.co.uk

NORWAY

Carlo Gavazzi AS
Melkeveien 13,
N-3919 Porsgrunn
Tel: +47 35 93 0800
Fax: +47 35 93 08 01
post@gavazzi.no

SWITZERLAND

Carlo Gavazzi AG
Verkauf Schweiz/Vente Suisse
Sumpfstrasse 3,
CH-6312 Steinhausen
Tel: +41 41 747 4535
Fax: +41 41 740 45 40
info@carlogavazzi.ch

FINLAND

Carlo Gavazzi OY AB
Petaksentie 2-4,
FI-00630 Helsinki
Tel: +358 9 756 2000
Fax: +358 9 756 20010
myynti@gavazzi.fi

PORTUGAL

Carlo Gavazzi Lda
Rua dos Jerónimos 38-B,
P-1400-212 Lisboa
Tel: +351 21 361 7060
Fax: +351 21 362 13 73
carlogavazzi@carlogavazzi.pt

OUR SALES NETWORK IN THE AMERICAS

USA

Carlo Gavazzi Inc.
750 Hastings Lane,
Buffalo Grove, IL 60089, USA
Tel: +1 847 465 6100
Fax: +1 847 465 7373
sales@carlogavazzi.com

CANADA

Carlo Gavazzi Inc.
2660 Meadowvale Boulevard,
Mississauga, ON L5N 6M6, Canada
Tel: +1 905 542 0979
Fax: +1 905 542 22 48
gavazzi@carlogavazzi.com

MEXICO

Carlo Gavazzi Mexico S.A. de C.V.
Calle La Montaña no. 28, Fracc. Los Pastores
Naucalpan de Juárez, EDOMEX CP 53340
Tel & Fax: +52.55.5373.7042
mexicosales@carlogavazzi.com

BRAZIL

Carlo Gavazzi Automação Ltda.Av.
Francisco Matarazzo, 1752
Conj 2108 - Barra Funda - São Paulo/SP
Tel: +55 11 3052 0832
Fax: +55 11 3057 1753
info@carlogavazzi.com.br

OUR SALES NETWORK IN ASIA AND PACIFIC

SINGAPORE

Carlo Gavazzi Automation Singapore Pte. Ltd.
61 Tai Seng Avenue #05-06
Print Media Hub @ Paya Lebar iPark
Singapore 534167
Tel: +65 67 466 990
Fax: +65 67 461 980
info@carlogavazzi.com.sg

MALAYSIA

Carlo Gavazzi Automation (M) SDN. BHD.
D12-06-G, Block D12,
Pusat Perdagangan Dana 1,
Jalan PJU 1A/46, 47301 Petaling Jaya,
Selangor, Malaysia.
Tel: +60 3 7842 7299
Fax: +60 3 7842 7399
sales@gavazzi-asia.com

CHINA

Carlo Gavazzi Automation
(China) Co. Ltd.
Unit 2308, 23/F.,
News Building, Block 1, 1002
Middle Shennan Zhong Road,
Shenzhen, China
Tel: +86 755 83699500
Fax: +86 755 83699300
sales@carlogavazzi.cn

HONG KONG

Carlo Gavazzi Automation
Hong Kong Ltd.
Unit 3 12/F Crown Industrial Bldg.,
106 How Ming St., Kwun Tong,
Kowloon, Hong Kong
Tel: +852 23041228
Fax: +852 23443689

OUR COMPETENCE CENTRES AND PRODUCTION SITES

DENMARK

Carlo Gavazzi Industri A/S
Hadsten

MALTA

Carlo Gavazzi Ltd
Zejtun

ITALY

Carlo Gavazzi Controls SpA
Belluno

LITHUANIA

Uab Carlo Gavazzi Industri Kaunas
Kaunas

CHINA

Carlo Gavazzi Automation (Kunshan) Co., Ltd.
Kunshan

HEADQUARTERS

Carlo Gavazzi Automation SpA
Via Milano, 13
I-20020 - Lainate (MI) - ITALY
Tel: +39 02 931 761
info@gavazziautomation.com



CARLO GAVAZZI
Automation Components

Energy to Components!

www.gavazziautomation.com

