


Charging Forward with Portable Power for Hybrid & Electric Vehicles

General Cable's new line of Carol® Brand CarolGrene™ Ultra Flex® EV Cables supplies charging power for all electric vehicles on the market today and is compatible with commercial and residential charging applications.

The CarolGrene Electric Vehicle cable line, when terminated in accordance with electric vehicle industry standards, is the most comprehensive product offering with three standard jacket types:

- CarolGrene EV All-Rubber Jacket offers the most flexible, durable cord with superior chemical and abrasion resistance to withstand daily abuse and temperature extremes in the harshest of environments; ideal for commercial and industrial applications
- CarolGrene EVE Thermoplastic Elastomer (TPE) Jacket lightweight for easy handling, superior flexibility in comparison to other TPE jackets, and can be molecularly bonded to caps and connectors for lasting strength, even in rough applications
- CarolGrene EVT Polyvinylchloride (PVC) Jacket the most economical of the three standard jacketed EV cables in the line; lightweight and best suited for consumer or home charging applications






- Custom jacket type and color
- · Your name printed directly to the jacket for private labeling
- Customized construction to suit any type of applications, including options for power, signal, data and fiber hybrid cables in any AWG size

CarolGrene cables are built to the following standards:

- UL 62 approved
- Compatible with SAE J1772 connectors and UL 2594 and NEC 625 charging stations
- · RoHS Compliant for EV charging stations in wet locations

Whether it's providing superior engineering support for new product innovation, solving a specific application problem, or answering a technical question, General Cable's Carol Brand Wire Wizards make magic happen. With over 50 years of experience behind us and an intense focus on Lean Sigma practices and extensive certifications, including the ISO/TS 16949 certification, Carol® Brand leads the industry in quality and innovation. We are focused on one goal – fulfilling your needs with quality products, availability and service







CarolGrene™ Ultra Flex® Type EVJ/EVJE/EVJT and EV/EVE/EVT

105°C, 300 and 600 Volt, UL/CSA Electrical Vehicle Charging Cord





				NOMINAL INS. THICKNESS		NOMINAL JACKET O.D.			APPROX.	
CATALOG Number	NO. OF COND.	AWG SIZE	COND. STRAND	INCHES	mm	INCHES	mm	CURRENT AMPS ⁽¹⁾	NET WT. LBS/M'(S)	STD. CTN.
			UL TY	PE EVJ,	EVJE, E	VJT - 30	0 VOLT	,		
EVJ143	3	14	41/30	0.030	0.76	0.390	9.91	18	105	1000'
	1	18	16/30	0.030	0.76					
EVJ123	3	12 18	65/30 16/30	0.030	0.76 0.76	0.455	11.56	25	130	1000'
	3	14	41/30	0.030	0.76					
EVJE143	1	18	16/30	0.030	0.76	0.390	9.91	18	87	1000'
EVJE123	3	12	65/30	0.030	0.76	0.454	11.53	25	125	1000'
	1	18	16/30	0.030	0.76					
EVJT143	3	14	41/30	0.030	0.76	0.390	9.91	18	88	1000'
	1	18	16/30	0.030	0.76					
EVJT123	3	12	65/30	0.030	0.76	0.454	11.53	25	127	1000'
	1	18	16/30	0.030	0.76					
		10				VT - 600	VOLT			
EV1403	3	14	41/30	0.045	1.14	0.545	13.84	18	180	1000'
	1	18	16/30	0.030	0.76					
EV1203	3	12	65/30	0.045	1.14	0.580	14.73	25	210	1000'
	1	18	16/30	0.030	0.76					
EV1003	3	10	104/30	0.045	1.14	0.620	15.75	30	270	1000'
	1	18	16/30	0.030	0.76					
EV0803	3	8	133/29	0.060	1.52	0.900	22.86	40	510	1000'
	1	18	16/30	0.030	0.76					
EVE1403	3	14	41/30	0.045	1.14	0.560	14.22	18	150	1000'
	1	18	16/30	0.030	0.76					
EVE1203	3	12	65/30	0.045	1.14	0.588	14.94	25	181	1000'
	1	18	16/30	0.030	0.76					
EVE1003	3	10	105/30	0.045	1.14	0.675	17.15	30	249	1000'
	1	18	16/30	0.030	0.76					
EVE0803	3	8	168/30	0.060	1.52	0.895	22.73	40	415	1000'
	1	18	16/30	0.030	0.76					
EVT1403	3	14	41/30	0.045	1.14	0.560	14.22	18	155	1000'
	1	18	16/30	0.030	0.76					
EVT1203	3	12	65/30	0.045	1.14	0.588	14.94	25	186	1000'
	1	18	16/30	0.030	0.76					
EVT1003	3	10	105/30	0.045	1.14	0.675	17.15	30	255	1000'
	1	18	16/30	0.030	0.76					
EVT0803	3	8	168/30	0.060	1.52	0.895	22.73	40	427	1000'
	1 1	18	16/30	0.030	0.76		1	1		

⁽¹⁾ Ampacities based on 90°C conductor and 30°C ambient temperature per Table 400.5(A) of the National Electrical Code®.

0.76

0.030

Product Construction

Conductors

 18 through 8 AWG fully annealed stranded bare copper per ASTM B-174

Inculation

- Thermoplastic Elastomer
- · Color Code

Jacket

- Ultra Flex® Thermoplastic Elastomer, black, Carolprene® rubber or custom color
- Temperature Range: -50°C to +105°C

Jacket Marking

 CAROLGRENE ULTRA FLEX® ELECTRIC VEHICLE CABLE - E333326-8 (UL) 3 COND 10 AWG + 1 COND 18 AWG 105C DRY 60C WET 600 V EVE

Applications

- Level 1 120 volt charging units
- Level 2 240 volt charging units
- Compatible with SAE J1772 EV plug standard
- UL 2594 and NEC 625 residential and commercial charging stations
- Ideal for electric vehicles (EV), neighborhood electric vehicles (NEV), battery electric vehicles (BEV), hybrid vehicles, low-speed vehicles (LSV), personal electric vehicles (PEV), plug-in hybrid vehicles (PHV) and plug-in hybrid electric vehicles (PHEV)

Features

- · Superior flexibility
- · Lightweight
- Oil-resistant jacket
- · Non-marking
- · Excellent molding characteristics
- · Water-resistant jacket, insulation and fillers

Industry Approvals

- UL 62 for Type EVE/EVJE/EV/EVJ
- RoHS Compliant
- UL Listed and c(UL) Listed for Indoor or Outdoor Use (18-10 AWG)

Other AWG sizes, conductor counts and put-ups available on special order.











18

16/30

⁽S) Actual shipping weight may vary.