

Lithium-Ionen – Standard Packs

rechargeable

DYNAMIS Li-Ion batteries from cells of well-known manufacturers and **UL-recognized** components.



All batteries (in shrink tube) are equipped with **PCM** and **150mm wire**.

For easy implementation in your application, all batteries already comply with **UN section 38.3 transportation test**.

The custom-built PCM ensures high safety during operation.

Order no.	Type	incl. NTC	Nominal Capacity (mAh)	Nominal Voltage (V)	Max. continuous discharge (A)	Dimension (mm) ca.	Weight (g)
60.16211	1S1P Panasonic NCR18650BL	no	3350	3.6	6	19/69	53
60.16212		yes				19/69	53
60.16215	2S1P Panasonic NCR18650BL	no	3350	7.2	6	38/19/69	105
60.16216		yes				38/19/69	105
60.16217	3S1P Panasonic NCR18650BL	no	3350	10.8	6	57/19/70	149
60.16218		yes				57/19/70	149
60.16219	4S1P Panasonic NCR18650BL	no	3350	14.4	6	75/19/70	205
60.16220		yes				75/19/70	205

Li-Ion Batteries can be customized to fulfill your special needs.

Possible features for customized Li-Ion Batteries:

- Different connector types
- Single-cell balancing
- Integrated charging circuits
- Fuel Gauge

Detailed datasheets available upon request.