WAGO INTERFACE ADAPTERS, 857 SERIES

For System Wiring

WAGO's Interface Adapters quickly connect the WAGO-I/O-SYSTEM to 857 Series Relay/Optocoupler Modules and JUMPFLEX® Signal Conditioners via pre-assembled WAGO 706 Series Interface Cables.

- Simple plug-in connection via jumper slot
- Combines 8 channels within a 857 Series module assembly
- Integrated test ports for each channel



857-98

| | WAGO-I/O-SYSTEM 750 | | | WAGO Interface Cables | | | WAGO Interface Adapters | |
|-------|---------------------|----------------------|---|------------------------------------|------------------|--|--|--------------------|
| | | Item Number | I/O Modules | | Item Number | | Item Number | Connection Example |
| Ճ | 1 | 750-1400 750-1402 | 16 DI 24 VDC 3.0 ms 16 DI 24 VDC 3.0 ms, low-side switching | 20/2x14 | 706-7753/304-xxx | 111111 | 857-982 with 14-pole pluggable connector per DIN 41651, high-side switching output | |
| 00 | 1 | 750-1500 | 16 DO 24 VDC 0.5 A | 20/2x15 | 706-7753/306-xxx | The state of the s | 857-986 with D-sub male connector, high-side switching input | |
| | | | | 20/2×14 | 706-7753/304-xxx | Trans. | 857-981 with 14-pole pluggable connector per DIN 41651, high-side switching input | |
| og/lg | 10 | 750-1502 | 8 DI 8 DO 24 VDC 0.5 A | (11111111) (1111111) 20/2x14 | 706-7753/304-xxx | The state of the s | 857-982 with 14-pole pluggable connector per DIN 41651, high-side switching output | |
| | | | | | | ALL SECTION OF THE PARTY OF THE | 857-981 with 14-pole pluggable connec- tor per DIN 41651, high-side switching input | |
| | | | | Opple former comments | 706-7753/306-xxx | Service of the servic | 857-986 with D-sub male connector, high-side switching input | |
| | | | | 16/16 | 706-753/301-xxx | | 857-980 with 16-pole pluggable connector per DIN 41651, suitable for JUMPFLEX® Signal Conditioners | |
| | | | | | 706-753/300-xxx | Total Street | 857-981 with 14-pole pluggable connector per DIN 41651, high-side switching input | |
| | | | | (14/14 | • | STATE OF THE PARTY | 857-982 with 14-pole pluggable connector per DIN 41651, high-side switching output | |

WAGO's Interface Cables are available in 1 m (-100), 2 m (-200) and 3 m (-300) lengths; they are also available with free ends. Additional cable types and lengths available upon request.



