

glueit



www.acme-glue.com

MATERIAL SAFETY DATA SHEET www.glueitgreen.com

	PRODUCT #FE-7004A
SECTIO	N 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION
COMPANY INFORMATION	DISTRIBUTOR INFORMATION
H.B. Fuller Company	American Chemical, Inc.
1200 Willow Lake Boulevard	2201 North 2nd Street
Vadnais Heights, MN 55110	Minneapolis, MN 55411
	(612) 522-4707
	dical Emergency Phone Number (24 hour): 1-888-853-1758
Transp	ort Emergency Phone Number (CHEMTREC): 1-800-424-9300
PRODUCT INFORMATION	
Product Number:	FE7004A
Product Description:	Epoxy resin
Product Identifier:	802489PM
	SECTION 2 – HAZARDS IDENTIFICATION
EMERGENCY OVER VIEW	
PHYSICAL STATE:	Liquid
COLOR:	Milky White
ODOR:	Sweet
Combustible	
Moderate to serve eye irritant.	
Causes skin irritation. May cause a	llergic skin reaction.
Moderate respiratory tract irritant.	
Harmful if swallowed.	
POTENTIAL HEALTH EFFECTS B	
	erate to serve eye irritation. Eye contact may result in tearing and reddening, but not likely emporary vision impairment (cloudy or blurred vision) is possible.
	tory irritation, defatting, and dermatitis. Not likely to cause permanent damage. May cause
sensitization.	tory initiation, defailing, and definations. Not likely to cause permanent damage. May cause
	e respiratory irritation. Inhalation of dusts produced during cutting, grinding or sanding of
this product may cause irritation of	
	aterials that may be hazardous when present as an airborne dust. During normal handling
	psulated within the product and will not present an exposure risk. Once the product has
	bed, dusting and exposure may occur.
	ticipated route of exposure. Harmful if swallowed. Irritating to mouth, throat, and stomach.
-	· · · · · · · · · · · · · · · · · · ·
LONG-TERM (CHRONIC) HEALTH	1 EFFECTS

TARGET ORGAN (S): Skin Lungs

REGULATED CARCINOGEN STATUS:

Unless noted below, this product does not contain regulated levels of NTP, ACGH or OSHA listed carcinogens. EXISTING HEALTH CONDITIONS AFFECTED BY EXPOSURE: Skin disease including eczema and sensitization; Lung disease

> 2201 North 2nd Street Minneapolis, MN 55411

PHONE > 800.2.GLUE.IT / 612.522.4707 800.245.8348

FAX > 800.8.GLUE.IT / 612.529.8645 800.845.8348

www.glueit.com

SECTION 3 - COMPOSITION/ IMFORMATION ON INGREDIENTS

Chemical Name	CAS#	PERCENT	
Bisphenol A diclycidyl ether	1675-54-3	50 - 70	
Epoxy resin	25068-38-6	10 - 30	
Butyl glycidyl ether	2426-08-6	5 – 10	
Silica, amorphous fumed	112945-52-5	1-5	

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910. 1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System Ingredient disclosure list. See section 8 for exposure limit guidelines.

	SECTION 4 – FIRST AID MEASURES
If In Eyes:	Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids
	often. Tilt the head to prevent chemical from transferring to the uncontaminated eye.
	Get immediate medical attention and monitor the eye daily as advised by your
	physician.
If On Skin:	Wash with soap and water. Remove contaminated clothing and launder. Get medical
	attention if irritation develops or persists.
If Vapors Inhaled:	Remove to fresh air. Restore breathing, if necessary. Call a physician if symptoms
	persists.
If Swallowed:	Do not induce vomiting. Seek Medical attention immediately. Drink two glasses of
	water or milk to dilute. Do no give anything by mouth to an unconscious person.
	Induced vomiting may lead to aspiration of the material into the lungs potentially
	causing chemical pneumonitis that may be fatal.
	SECTION 5 – FIRST FIGHTING MEASURES
Flash Point:	
	78°C; 172°F TCC
Auto Ignition Temperature:	Not established
Lower Explosive Limit (% in air):	Not established
Upper Explosive Limit (% in air):	Not established
Extinguishing Media:	Use water spray, foam, dry chemical or carbon dioxide.
Unusual Fire and Explosion Hazards:	Vapors are heavier than air and can travel to a source of ignition and flash back.
Special Fire Fighting Instructions:	Persons exposed to products of combustion should wear self-contained breathing
	apparatus and full protective equipment.
Hazardous Combustion Products:	Carbon dioxide, Carbon monoxide
	ECTION 6 – ACCIDENTAL RELEASE MEASURES
Special Protection:	Exposure to the spilled material may be irritating or harmful. Follow personal
	protective equipment recommendations found in Section 8 of this MSDS. Additional
	precautions may be necessary based on special circumstances created by the spill
	including; the material spilled, the quantity of the spill, the area in which the spill
	occurred. Evaporation of volatile substances can lead to the displacement of air
	creating an environment that can cause asphyxiation.
Cleanup:	Dike if necessary, contain spill with inert absorbent and transfer to containers for
	disposal. Keep spilled product out of sewers, watersheds, or water system. Shut off
	ignition sources; including electrical equipment and flames. Do no allow smoking in
	the area.
Transport Emergency Phone Number ((CHEMTREC): 1-800-424-9300
	SECTION 7 – HANDLING AND STORAGE
Handling:	Harmful or irritating material. Avoid contacting and avoid breathing the material. Use
······································	only in a well ventilated area. Keep away from heat, sparks, and flame. Wash
	thoroughly after handing. Keep container closed. Emptied container retains vapor
	and product residue. Observe all labeled precautions until container is cleaned.
	Drums of this material should be grounded when pouring. DO NOT CUT OR WELD
	ON OR NEAR THIS CONTAINER.
Storage:	Store in a cool, dry place, ventilated location. Keep away from heat and flame. Keep
ololage.	container closed.
Consult the Technical Data Sheet for s	
Sonsul the rechnical Data Sheet IUI S	ר ביות אינטימעט וואנו עטוטרוא.

Consult the Technical Data Sheet for specific storage instructions.

	SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION
Eye Protection:	Wear safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Have an eye wash station available.
Skin Protection:	Avoid skin contact by wearing chemically resistant gloves and long sleeved shirt. An apron may be appropriate if splashing can occur.
Gloves:	Nitrile
Respiratory Protection:	Respiratory protection may be required to avoid overexposure when handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. NIOSH approved air purifying respirator with dust/mist filter if product is sprayed. Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134).
Ventilation:	Use local exhaust-ventilation or other engineering controls to minimize exposures.

Exposure Limits.

Exposure Limits:		
Chemical Name	ACGI Exposure Limits	AIHA WEEL
Bisphenol A diglycidyl ether	Not established	Not established
Epoxy resin	Not established	Not established
Butyl glycidyl ether	TWA 3ppm Skin absorption may potentially	50ppm TWA;270 mg/m3 TWA
	contribute to the overall exposure to this material.	
Silica, amorphous fumed	Not established	20 mppcf TWA; ((80)/(%SiO2) mg/m3 TWA)

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES		
Physical State:	Liquid	
Color:	Milky white	
Odor:	Sweet	
Odor Threshold:	Not established	
Weight Per Gallon (lbs.):	9.6	
Specific Gravity:	1.15	
Solids (% by weight):	100.0	
pH:	Not established	
Boiling Point (deg. C):	Not established	
Freezing/Melting Point (deg. C):	Not established	
Vapor Pressure (mm Hg):	Not established	
Vapor Density:	Not established	
Evaporation Rate:	Not established	
Octanol/Water Coefficient:	Not established	
	SECTION 10 - STABILITY AND REACTIVITY	
Stability:	Stable under normal conditions	
Chemical Incompatibility:	Not established	
Hazardous Polymerization:	Will not occur.	
Hazardous Decomposition products:	Carbon monoxide, carbon dioxide	
SECTION 11 – TOXICOLOGICAL INFORMATION		

Chemical Name	LD50/LC50	
Bisphenol A diglycidyl ether	Oral LD50 Rat = 11.3 ml/kg	
	Dermal LD50 Rabbit=20000 mg/kg	
Epoxy resin	Oral LD50 Rat = 11.4 g/kg	
	Dermal LD50 Rabbit> 20 ml/kg	
Calcium carbonate	Oral LD50 Rat = 1660 mg/kg	
	Inhalation LC50 Rat = 1456ppm/4H	
	Dermal LD50 rabbit = 2520mg/kg	
Silica, amorphous fumed	Oral LD50 Rat 3160 mg/kg	
TOYIOOLOOX OLIMMA DV No additional hardthein famma ti		

TOXICOLOGY SUMMARY: No additional health information available

Overview:

SECTION 12 – ECOLOGICAL INFORMATION No ecological information available

SECTION 13 – DISPOSAL CONSIDERATIONS

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Dispose via incineration at an approved facility is recommended. Consult state, local or provincial authorities for more restrictive requirements.

SECTION 14 – TRANSPORTATION INFORMATION

Consult Bill of Lading for transportation information DOT: Not Regulated IATA: Not Regulated

SECTION 15 – REGULATORY INFORMATION		
INVENTORY STATUS		
U.S. EPA TSCA:	This product is in compliance with the Toxic Substances Control Act's Inventory requirements.	
Canadian CEPA DSL:	This product is in compliance with the Canadian Domestic Substance List requirements.	
European EINECS:	This product is in compliance with the European Inventory of Notified and Existing Chemical Substances requirements.	
Australia AICS:	This product is in compliance with the Australian Inventory of Chemical Substances requirements.	
Japan ENCS:	This product is in compliance with the Japanese Existing and New Chemical Substances requirements.	
Korean TCCL: Philippines:	This product is in compliance with the Korean Existing Chemicals List requirements. This product is in compliance with the Philippine Inventory of Chemical and Chemical Substances requirements.	

If you need more information about the inventory status of this product call 651-236-5858

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us to request an export review.

Federal Reporting

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical (s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 72. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CA\$#	%
	CAS#	76

WHMIS STATUS: Unless listed below, this product is not controlled under the Canadian Workplace Hazardous Materials Information System.

B3 D2B D1A

STATE REPORTING - This MSDS is not prepared for distribution in California.

SECTION 16 – ADDITIOINAL INFORMATION

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS)

HMIS RATING: HEALTH - - 2 FLAMMABILITY – 2 REACTIVITY – 0 See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for protective equipment recommendations.

Prepared by: The Global Regulatory Department Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B Fuller Company from its suppliers, and because the H.B Fuller Company has no control over the conditions of handling and use, the H.B Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.N Fuller Company products to comply with all applicable federal, state and local laws regulations.

01/16/2009