AC-760 MSDS

HEALTH HAZARDS:		C	OATE ISSUED: 02/01/09
HEALTH: FIRE: REACTIVITY: FLASH POINT:	2 1 0 >200°F	METHOD USED:	SETA
PRODUCT NAME EL-CAST 760			COMMON CODE:
HAZARD MATERIAL DESCRIPTION, PROPER SHIPPING NAME, HAZARD CLASS: Plastic material - Liquid NOIBN Not Restricted			
CHEMICAL FAMILY Epoxy Resin - Formula	ated		FORMULA Proprietary
HAZARDOUS INGREDIENTS			
CAS # 28064-14-4 25068-38-6 17557-23-2 KEY: LIMITS HAVE	% (optional)    NOT BEEN ESTABL	CHEMICAL NAMES Epoxy Resin Epoxy Resin Epoxy Resin ISHED	TLV/PEL   
<u>F</u>	HYSICAL & CHEM	CAL CHARACTERIS	<u>FICS</u>
Boiling Point:		>500°F	
Vapor Pressure:		0.03 at 77°C	
Vapor Density (air=1)		Not applicable	
Solubility in water:		Slight	
Specific gravity (H <sub>2</sub> O=	:1)	1.65	
Percent volatile by vol	lume (%):	0%	
Evaporation rate: ( =	1):	ΝΑ	
Percent solid by weigl	nt (%):	100%	
Appearance and odor:		Black Liquid, slight	odor
Analytical: 13.6	lbs/gal		

#### FIRE AND EXPLOSION DATA

Flammable Limits:	LEL Not Established UEL Not established
Extinguishing Media:	Water, fog, foam, dry chemical, CO <sub>2</sub>
Special Fire Fighting Procedures:	Do not enter confined fire space without full protective gear including a positive pressure, self-contained, NIOSH approved breathing apparatus. Cool fire exposed container with water.
Unusual Fire and Explosion Hazard:	Container areas exposed to intense heat or flame should be cooled with $H_2O$ to prevent pressure build-up and/or weakening of container structure.

## **REACTIVITY DATA**

Stability:	Stable
Conditions to Avoid:	Avoid high temperatures, open flames and unscheduled contact with curing agents.
Incompatibility: (Materials to Avoid)	Incompatible with strong oxidizing agents, strong acids and bases, secondary aliphatic amines and mercaptans.
Hazardous Decomposition Products: Hazardous Polymerization:	Carbon dioxide (CO <sub>2</sub> ) Carbon Monoxide (CO), aldehydes, acids and other organic substances may be formed during high temperature degradation. Will not occur.
Conditions to Avoid:	Avoid mixing resin and hardener in uncontrollable quantities.

## HEALTH HAZARD DATA

Chemical Listed as Carcinogen or Potential Carcinogen in NTP, IARC or OSHA 1910(Z) This material is neither carcinogenic or potentially carcinogenic.

**EFFECTS OF OVEREXPOSURE** 

Skin Contact:	Product could be moderately irritating to skin. May cause allergic skin reaction in susceptible individuals. Avoid direct skin contact when using	
	this material.	
Fue Contests	Draduct could be mederately irritating to the avec. Avoid touching avec	
Eye Contact:	Product could be moderately irritating to the eyes. Avoid touching eyes when using this material.	
Inhalation:	Because of its low volatility this product is not likely to be an inhalation hazard.	
Ingestion:	No adverse effects anticipated by this route of exposure incidental to proper industrial handling.	
Primary Routes of Entry:		
Inhalation:	Skin Contact Other (Specify)	
EMERGENCY AND FIRST AID PROCEDURES:		

- **Inhalation:** Remove victim to fresh air.
- Eyes:Flush eyes with generous amounts of water for a least 15 minutes.GETMEDICAL ATTENTION if it appears necessary.
- Skin: Wash thoroughly with soap and water.
- **Ingestion:** In general, no treatment is necessary unless large quantities of product are ingested.

#### **OCCUPATIONAL EXPOSURE LIMITS**

OSHA Permissible	OSHA limits have not been established for this product.
Exposure Limit:	

ACGIH Threshold ACGIH limits have not been established for this product. Limit Value:

SPECIAL PROTECTION INFORMATION		
SPECIAL PROTECTION INFORMATION		
<b>Respiratory Protection:</b>	No respiratory protection should be needed.	
Ventilation:	Local exhaust is recommended. Mechanical exhaust can be used as a back up system.	
Protective Gloves:	Chemical resistant gloves such as PVA.	
Eye Protection:	NIOSH approved safety glasses or goggles with side shields.	
Other Protective Clothing or Equipment:	Chemical resistant clothing as required to minimize skin contact.	
	SPILL OR LEAK PROCEDURES	
Steps to be Taken in Case Use cautious judgment when cleaning spills. Small spills   Material is Released or Spilled: Use cautious judgment when cleaning spills. Small spills   may be collected with absorbent material, such as clay or sand. Large spills should be diked and contained with absorbent materials. Flush area with water spray to remove residue. Dispose of flush legally.		
Waste Disposal Methods:	Dispose in accordance with local, state and federal regulations.	
	SPECIAL PRECAUTIONS	
Precaution to be Taken in Handling and Storage:	Store at ambient temperatures in well ventilated area. Avoid sparks, open flames and extreme heat. Store separately from amine curing agents. Protect container from physical damage.	
Other Precautions:	Container, even those that have been emptied, can contain product residues. Handle in accordance with good industrial practices. Avoid prolonged or repeated contact with skin. Wash with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet facilities. Launder contaminate clothing before use.	

# KEY ---- Limits have not been establishedNA - Not ApplicableUI - Unavailable Information

The information supplied here is based on data we consider to be accurate. No warranty, expressed or implied is made. This information is offered solely for you consideration, interpretation and information.