







www.glueit.com

www.glueitgreen.com

www.acme-glue.com

#### TECHNICAL DATA SHEET

### PRODUCT #AC-11606-Red

### **Description:**

AC-11606 High Temp Red Silicone is a high quality, single-component, 100% silicone sealant which contains no solvents or fillers. Use in high heat applications not exceeding 650° F (343° C). It adheres to metal, glass, marble, tile, ceramic, porcelain, painted surfaces, non-oily woods, and rubber. It can be used as an adhesive for bonding surfaces together.

### **Typical Properties, As Supplied:**

RTV:	
Color:	Red
Specific Gravity at 77° (25°C)	
Extrusion Rate (3.18 mm orifice, 90 psi air	
Pressure) g/min:	400
Flow, Sag, Slump:	NIL
Application Temperature Range, °F (°C)	34 to 140 (-37 to 60)
Tooling Time, Minutes:	5-11
Tack Free Time, Minutes:	
Cure Time at 77°F (25°C) and 50% RH	
(3.18 mm thickness), hrs.:	24
Typical Properties, As Cured (7 Days)	
Durometer Hardness, Shore A, Points (ASTM 2240):	30
Tensile Strength, Mpa (psi) (ASTM D412):	4 (375)
Elongation, percent (ASTM D412):	600
Brittle Point, F (C) (ASTM D746):	100 (-38)
Peel Strength, ppi:	20
Temperature Range:	
Continuous operating temperature, Max:	450° F (232° C)
Intermittent operating temperature, Max:	

# **Specifications:**

USDA for use in federally inspected meat and poultry plants, FDA reg. #21, CFR 177.2600, TT-S-0015443A (COM-NBS) Class A, TT-S00230C (COM-NBS) Class A Mil-A-46106B Amend. 3, Type 1. Canadian 19-GP-9MA type 1. Conforms to NSF Standard 51.

### **Limitations:**

AC-11606-Red High Temp Sealant is not recommended for use in applications involving:

- Temperatures exceeding 650° F (343° C)
- Structural silicone glazing
- Prolonged water immersion
- Porous water immersion
- Materials that bleed oils or solvents
- Surfaces to be painted...conventional paints will not adhere

## Packaging:

 $AC-11606 \ Red \ High \ Temp \ Silicone \ is \ supplied \ in \ a \ 10.1 \ oz \ (300ml) \ caulking \ cartridge, 7.25 \ oz \ pressurized \ can, 3 \ oz \ squeeze \ tube, 5 \ gallon \ pails, and 55 \ gallon \ drums$ 

## **Warranty and Shelf Life:**

Each application should be pre-tested for suitability of this product for the intended use. When stored in the original, unopened container at temperatures less than 90° F (32° C), AC-11606 Red High Temp Silicone is guaranteed for one year from date of purchase.