

# Quad 10Ω SPDT Analog Switch

## Features

- Low ON-State Resistance
- Low Charge Injection
- Excellent ON Resistance Matching
- +2.3V to +5.5V Single-Supply Operation
- Low Total Harmonic Distortion
- Low Supply Current (<1μA)
- Break-before-make Enable Circuitry
- Control Inputs are 5-V Tolerant
- TSSOP-16 and SSOP-16 Package are Available

## Applications

- Cell Phones
- PDAs
- Portable Instrumentation
- Audio and Video Signal Routing
- Sample-and-Hold Circuit
- Battery-Powered Equipment
- Communication Circuit

## General Description

The G3204 is a quad low on-resistance, SPDT (Single-Pole/Double-Throw) analog switch that operates from a 2.3V to 5.5V supply. The device offers an excellent ON-resistance matching, and low total harmonic distortion (THD) performance. These features make this device suitable for portable audio applications.

The G3204 is available in the TSSOP-16 and SSOP-16 package.

## Ordering Information

ORDER NUMBER	MARKING	TEMP. RANGE	PACKAGE (Pb free)
G3204D61U	G3204	-40°C to 85°C	TSSOP-16
G3204S11U	G3204	-40°C to 85°C	SSOP-16

Note: D6: TSSOP-16 S1: SSOP-16  
 1: Bonding Code  
 U: Tape & Reel

## Pin Configuration

