



COMPONENT BODY DIAMETER	DISTANCE BETWEEN COMPONENTS	INSIDE TAPING SPACE		
		I	II	III
INCHES [mm]	±0.020 [0.5mm]	±0.059 [1.5mm]		
0.0 to 0.197 [0mm to 5mm]	0.2 [5mm]	2.062 [52.4mm]	2.5 [63.5mm]	2.874 [73mm]
0.197 to 0.394 [5.01mm to 10mm]	0.4 [10mm]	2.062 [52.4mm]	2.5 [63.5mm]	2.874 [73mm]
0.394 to 0.591 [10.01mm to 15mm]	0.6 [15mm]	2.062 [52.4mm]	2.5 [63.5mm]	2.874 [73mm]

Note: Our standard packaging is class I. Class II class III are per request

NEXT ASSEM	USED IN	LTR.	REVISION	BY	DATE
Part #:		<b>Thru-Hole Inductor Tape Specification</b>			
DRAWN BY	KB	APPROVED BY	KB	ENG	QA
					MFG

Unless otherwise specified dimensions are in inches.  
in. (mm)

This drawing or specification is the property of Gowanda Electronics. Copies shall not be reproduced or copied or used as the basis for the manufacture or sale of apparatus without permission.



ONE MAGNETICS PARKWAY  
P.O. BOX 111  
GOWANDA, NEW YORK 14070

Phone Number: (716)532-2234  
Website: www.gowanda.com