

TG-679 Expanded Graphite Powder

Technical Data Sheet 456

Product Overview

GRAFOIL grade TG-679 is an expanded natural graphite powder with consistent purity and good lubrication properties. Typical applications include using the graphite powder as an electrically conductive additive or as a thermal transfer enhancement in plastics and foams or as a lubricant. TG-679 GRAFOIL has a unique combination of very thin and small diameter plate-like particles.

Typical Properties*

Characteristic	Unit	Value
Ash	%	2.25
Moisture	%	0.2
Sulfur	ppm	500
Al	ppm	1000
Ba	ppm	4
Ca	ppm	2600
Cr	ppm	4
Cu	ppm	9
Fe	ppm	2100
Mg	ppm	1600
Mn	ppm	16
Mo	ppm	12
Si	%	0.5
Ti	ppm	70
V	ppm	5
Typical Density A.D. (Scott)	g/cm ³	0.05
Surface Area	m ² /g	20
Typical Particle Distribution d90%	µm	65.2
d50%	µm	20
Typical Particle Thickness	µm	2.5
Packaging Paper Bag	kg	8

Notes:

* Properties listed are typical and cannot be used as accept/reject specifications.

+1 (800) 253-8003 (Toll-Free in USA)

+1 (216) 529-3777 (International)

www.graftech.com | www.grafoil.com

grafoil@graftech.com

Redefining limits

© 2011 GrafTech International Holdings Inc. This information is based on data believed to be reliable but GrafTech makes no warranties, express or implied, as to its accuracy and assumes no liability arising out of its use. The data listed falls within the normal range of product properties but should not be used to establish specification limits or used alone as the basis of design. GrafTech's liability to purchasers is expressly limited to the terms and conditions of sale. GRAFOIL, EXPANDOGRAF, GRAFKOTE, GTS, RIBBON-PACK and SUPER GTO are registered trademarks of GrafTech International Holdings Inc. GRAFOIL flexible graphite materials, and processes are covered by several US patents. For patent information visit www.grafoil.com/patents.