

AGSX-114 Graphite

Technical Data Sheet 6027

Product Overview

GRAFSTAR™ AGSX-114 graphite is specially engineered to greatly reduce degradation due to oxidation at temperatures as high as 750°C. This oxidation resistant grade has been shown to have product life 4 to 6 times that of standard graphite materials in oxygen rich, high temperature processes. The oxidation resistance is stable and does not drop off in high humidity environments.

AGSX-114 graphite should be used in all applications requiring high product density, good mechanical properties and strong protection against oxidation.

Applications

- Aluminum pumps
- Aluminum disperers/impellers
- Aluminum degassing shapes/rotors
- Aluminum degassing volute case/rotors

Sizes*

Shape	Measurement	Unit	Value	Unit	Value
Round	Diameter	in	3 - 9 x 72	mm	75 - 225 x 1830
Rectangle	Length	in	Available in 40, 48, 60, 65, 72	mm	Available in 1015, 1220, 1525, 1650,1830

Typical Properties at Room Temperature**

Characteristic	Unit	WG	AG	Unit	WG	AG
Density	lbs/ft³	107		g/cm³	1.72	
Maximum Particle Size	inches	0.03		mm	0.76	
Specific Resistance	10⁴Ωin	2.8	3.9	μΩm	7	10
Flexural Strength	psi	3350	2200	MPa	23	15

(Typical Properties continued on next page)

Typical Properties at Room Temperature** (continued)

Characteristic	Unit	WG	AG	Unit	WG	AG	
Young's Modulus	10º psi	1.9	1.0	GPa	13	7	
Tensile Strength	psi	2750	1600	MPa	19	11	
Compressive Strength	psi	6500		MPa	45		
Permeability	Darcy	0.008	0.004	Darcy	0.008	0.004	
Thermal Conductivity	tivity BTU-ft/hr ft² °F		70	W/mK	170	120	
CTE (RT to 100 °C)	10 ⁻⁶ /°F	0.7	1.7	10 ⁻⁶ /K	1.2	3.1	
Ash Content	%	0.15		%	0.	0.15	
Porosity	%	1	16	%	16		
Oxidation Rate at 750°C	lbs/ft²/hr	0.067		gm/m²/hr	325		

United States of America 101 N. Philippi Pike Anmoore, WV 26323-0120 Ph: +1-800-842-8805 +1-304-624-1253

Redefining limits

France La Lechere 73264 Aigueblanche Cedex, France Ph: +33-4-79-41-45-00

^{*}Other sizes available upon request
** Properties listed are typical and cannot be used as accept/reject specifications