

FUSE & CIRCUIT PROTECTION

FUSIBLE ET PROTECTION DE CIRCUIT • PROTECCIÓN DE FUSIBLE Y CIRCUITO

ATO®/ATC® BLADE FUSE • FUSIBLE À LAMES ATO^{MD}/ATC^{MD} • FUSIBLE DE CUCHILLA ATO®/ATC®

ATO®/ATC® Blade Fuses with LED Indicator



Fast Acting/Blade Mounting

A cost-effective standard automotive fuse for use in automotive, battery and general DC applications.


Body Material: Nylon PA 66

Electrical Specifications: 3A-30A, 32VDC

Design Standards: ISO 8820 Standard Specifications

SPECIFICATIONS

- Voltage: 32VDC
- Amperage: 2A, 3A, 5A, 7.5A, 10A, 15A, 20A, 25A, 30A,
- Terminals: Zinc alloy
- Designed to meet SAE and ISO Standards
- Interrupt Rating – 1000A @ 32 VDC



82-ANR-I-10A



82-ANR-I-15A



82-ANR-I-20A



82-ANR-I-25A



82-ANR-I-30A

Part No.	Current Rating	Color	Pack	Description
82-ANR-I-3A	3A	VIOLET	2	ATO® Fuse with LED Indicator
82-ANR-I-5A	5A	TAN	2	ATO® Fuse with LED Indicator
82-ANR-I-7.5A	7.5A	BROWN	2	ATO® Fuse with LED Indicator
82-ANR-I-10A	10A	RED	2	ATO® Fuse with LED Indicator
82-ANR-I-15A	15A	BLUE	2	ATO® Fuse with LED Indicator
82-ANR-I-20A	20A	YELLOW	2	ATO® Fuse with LED Indicator
82-ANR-I-25A	25A	CLEAR	2	ATO® Fuse with LED Indicator
82-ANR-I-30A	30A	GREEN	2	ATO® Fuse with LED Indicator
82-ANR-I-5	(10A, 15A, 20A, 25A, 30A)		5	ATO® Fuse with LED Indicator Assortment

ATO®/ATC® Fuse Holders



82-2209



82-2207



82-2166



82-2165



82-2164



84-2903



82-2212

Part No.	Current Rating	Color	Pack	Description
82-2209	20A (14GA)	RED	1	ATO®/ATC® with Protective Cap + 20A Fuse, 7"
82-2207	20A (16GA)	RED	1	ATO®/ATC® with Protective Cap, 7"
82-2166	30A (12GA)	ORANGE	1	ATO®/ATC® w/Protective Cap & Mounting Tab, 10"
82-2165	30A (12GA)	ORANGE	1	ATO®/ATC®, Continuous Loop, 8"
82-2164	20A (14GA)	BLACK	1	ATO®/ATC®, Blunt Cut, 7"
84-2903	20A (14-18GA)		1	Self Stripping ATO®/ATC® Fuse Holder
82-2212	25A Primary Circuit, 15A Auxiliary Circuit, (Total not to exceed 30A combined)	RED	1	"Add-A-Fuse" ATO®/ATC® Fuse Holder; 16GA

ATO®/ATC® Blade Fuses



82-ANR-3A



82-ANR-5A



82-ANR-7.5A



82-ANR-10A



82-ANR-15A



82-ANR-20A



82-ANR-25A



82-ANR-30A

Part No.	Current Rating	Color	Pack	Description
82-ANR-2A	2A	GRAY	5	ATO® Fuse
82-ANR-3A	3A	VIOLET	5	ATO® Fuse
82-ANR-5A	5A	TAN	5	ATO® Fuse
82-ANR-7.5A	7.5A	BROWN	5	ATO® Fuse
82-ANR-10A	10A	RED	5	ATO® Fuse
82-ANR-15A	15A	BLUE	5	ATO® Fuse
82-ANR-20A	20A	YELLOW	5	ATO® Fuse
82-ANR-25A	25A	CLEAR	5	ATO® Fuse
82-ANR-30A	30A	GREEN	5	ATO® Fuse
82-ANR-7	(5A, 7.5A, 10A, 15A, 20A, 25A, 30A)		7	ATO® Fuse Assortment
82-ANR-7P	(5A, 7.5A, 10A, 15A, 20A, 25A, 30A)		8	ATO® Fuse Assortment & Puller
82-ANR-6T	(5A, 10A, 15A, 20A, 25A, 30A)		7	ATO® Fuse Assortment & Tester
82-ASST-44	(5A, 10A, 15A, 20A, 25A, 30A)		43	ATO® Fuse Assortment & Tester
82-ASST-53	(10A, 15A, 20A, 30A) + (30A, 40A, 50A)		45	ATO® & MAXI Fuse Assortment & Tester
82-ASST-80R	(3A, 5A, 7.5A, 10A, 15A, 20A, 25A, 30A)		80	ATO®/ATC® Fuse Assortment
82-ASST-180			180	Low Profile MINI®, MINI®/ATM, & ATO®/ATC® Fuse Assortment



Warning: Operation beyond the specified maximum ratings or improper use may result in damage and possible electrical arcing and/or flame. Avoid contact of device with chemical solvent. Prolonged contact will damage the device performance.

MICRO2[®] is a registered trademark of Littelfuse. ATO[®] is a registered trademark of Littelfuse. ATC[®] is a registered trademark of Cooper Bussmann. JCASE[®] is a registered trademark of Littelfuse. MINI[®] is a registered trademark of Littelfuse. MICRO2[™] est une marque de commerce de Littelfuse. ATO[™] est une marque de commerce de Littelfuse. ATC[™] est une marque de commerce de Bussman. JCASE[™] est une marque de commerce de Littelfuse. MINI[™] est une marque de commerce de Littelfuse. MICRO2[®] es una marca comercial registrada de Littelfuse. ATO[®] es una marca comercial registrada de Littelfuse. ATC[®] es una marca comercial registrada de Bussman. JCASE[®] es una marca comercial registrada de Littelfuse. MINI[®] es una marca comercial registrada de Littelfuse.