

Economy Swing-Out Wall Mount Cabinet *RB-SW Series*

130 lbs Weight Capacity

Features



RACK BASICS®



- Double-hinged for easy rear access (body swings open to 120°).
- Constructed in light duty 16-gauge steel.
- Includes two (2) pairs of EIA-310-D compliant square hole punched rails with 19" mounting.
 - Starter pack of M5 screws and cage nuts included.
 - For 10-32 hardware see the **CAGKIT Series**.
- Rails are adjustable.
- Includes one (1) locking lightly smoked tempered glass reversible front door (hinged on right side as standard).
- Includes one (1) pair of locking removable side panels.
- Front and side of frame includes venting for air flow.
- Top, bottom and rear cable access.
- Provision for optional fans on top panel.
- Middle body section is not reversible, and hinges on the left side.
- Ships assembled - ready to install.
- Finished in black powder paint.
- Tested to 130 lbs (59 kg) of equipment load capacity.
- RoHS Compliant.

Part of the Rack Basics® line of economy rack solutions.

To learn about our heavy duty version of the swing-out wall mount cabinet, [click here](#).

Gallery



Accessories

- Horizontal Ring Cable Manager
- Cable Lacing Bar
- Grill Fan Kits
- Mounting Hardware
- Universal Rack Shelf
- Horizontal Lacing Strip
- Outlet Strips

| Part No. | Overall Dimensions | | | Rack Units | Mounting Dimensions | | | Usable Depth |
|----------------|--------------------|-------|-------|------------|---------------------|-------|-------|--------------|
| | Height | Width | Depth | | Height | Width | Depth | |
| RB-SW9 | 19.90 | 23.62 | 21.65 | 9U | 15.75 | 19.00 | 16.13 | 18.25 |
| RB-SW12 | 25.15 | 23.62 | 21.65 | 12U | 21.00 | 19.00 | 16.13 | 18.25 |

| Part No. | Overall Dimensions | | | Rack Units | Mounting Dimensions | | | Usable Depth |
|----------------|--------------------|-------|-------|---------------|---------------------|-------|-------|-----------------|
| | Height | Width | Depth | | Height | Width | Depth | |
| RB-SW15 | 30.40 | 23.62 | 21.65 | 15U | 26.25 | 19.00 | 16.13 | 18.25 |
| RB-SW18 | 35.65 | 23.62 | 21.65 | 18U | 31.50 | 19.00 | 16.13 | 18.25 |

Note: Usable depth is the furthest depth equipment can be mounted for the cabinet's swing-out feature to function.

Data subject to change without notice

© 2017. Hammond Manufacturing Ltd. All rights reserved.