


| APPLICABLE STANDARD | | IEC 61076-3-124 | | | |
|---|--|---------------------------|---|---|----------|
| | Operating Temperature Range | -40°C TO +80°C(95%RH max) | Storage Temperature Range | -30°C TO +60°C(95%RH max) | |
| Rating | Voltage | 50 V AC / 60 V DC | Current | 1.5 A (all pins) Values at 20 °C | |
| | | | | 3.0 A (pin No.1, 2, 6 and 7) Values at 40 °C | |
| SPECIFICATIONS | | | | | |
| ITEM | TEST METHOD | | REQUIREMENTS | QT | AT |
| CONSTRUCTION | | | | | |
| General Examination | Examined visually and with a measuring instrument. | | According to drawing. | X | X |
| Marking | Confirmed visually. | | According to drawing. | X | X |
| ELECTRIC CHARACTERISTICS | | | | | |
| Contact Resistance | Measured at 100 mA max (DC or 1000 Hz). | | contact : 30 mΩ max. shield : 100 mΩ max. | X | — |
| Insulation Resistance | Measured at 500 V DC. | | 500 MΩ min. | X | — |
| Voltage Proof | 500 V DC applied for 1 min. Current leakage 2mA max. | | No flashover or breakdown. | X | — |
| Insertion loss | Measured in the range of 1 to 500 MHz. | | 0.02 √(f) dB max. (Whenever the formula results in a value less than 0.1 dB, the requirement shall revert to 0.1 dB.) | X | — |
| Return loss | Measured in the range of 1 to 500 MHz. | | 68 – 20log(f) dB min. (Whenever the formula results in a value greater than 30 dB, the requirement shall revert to 30 dB.) | X | — |
| Near end crosstalk | Measured in the range of 1 to 500 MHz. | | 94 – 20log(f) dB min. (1MHz to 250MHz) 46.04 – 30log(f/250) dB min. (250MHz to 500MHz) (Whenever the formula results in a value greater than 75 dB, the requirement shall revert to 75 dB.) | X | — |
| Far end crosstalk | Measured in the range of 1 to 500 MHz. | | 83.1 – 20log(f) dB min. (Whenever the formula results in a value greater than 75 dB, the requirement shall revert to 75 dB.) | X | — |
| Transverse conversion loss | Measured in the range of 1 to 500 MHz. | | 68 – 20log(f) dB min. (Whenever the formula results in a value greater than 50 dB, the requirement shall revert to 50 dB.) | X | — |
| Transverse conversion transfer loss | Measured in the range of 1 to 500 MHz. | | 68 – 20log(f) dB min. (Whenever the formula results in a value greater than 50 dB, the requirement shall revert to 50 dB.) | X | — |
| MECHANICAL CHARACTERISTICS | | | | | |
| Insertion And Withdrawal Forces | A maximum rate of 50 mm/min. measured with an applicable connector. | | Insertion force 25 N max. Withdrawal force 25 N max. | X | — |
| Mechanical Operation | 5000 times insertions and extractions. mating speed : 10 mm/s max. rest : 5s, min.(unmated) | | 1) Resistance: contact : 80 mΩ max. shield : 100 mΩ max. 2) No damage, cracks or looseness of parts. | X | — |
| Vibration | Frequency 10 to 500 Hz 0.35 mm, 50 m/s ² 2hrs in each of 3 mutually perpendicular axis. | | 1) No electrical discontinuity of 1μs. 2) No damage, cracks or looseness of parts. | X | — |
| | COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE |
| △ | | | | | |
| Note | | | APPROVED | RI.TAKAYASU | 17.02.01 |
| | | | CHECKED | KI.NAGANUMA | 17.01.31 |
| | | | DESIGNED | YS.SAKODA | 17.01.31 |
| Unless otherwise specified, refer to IEC 60512. | | | DRAWN | YS.SAKODA | 17.01.31 |
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test | | | DRAWING NO. | TELC-301076-00 | |
| HRS | SPECIFICATION SHEET | | PART NO. | IX61-A-10P | |
| | HIROSE ELECTRIC CO., LTD. | | CODE NO. | 251 | △ 1/3 |

| SPECIFICATIONS | | | | | |
|--|---|---|----------------|------------|---|
| ITEM | TEST METHOD | REQUIREMENTS | QT | AT | |
| Fretting Corrosion | 490 m/s ² , 30 times/min at 1000 times. | 1) No electrical discontinuity of 1μs. 2) No damage, cracks or looseness of parts. | X | — | |
| Shock | Subject mated specimens to 300 m/s ² half-sine shock pulses of 11 milliseconds duration, 3 shocks in both directions of 3 mutually perpendicular directions (totally 18 shocks) | 1) No electrical discontinuity of 1μs. 2) No damage, cracks or looseness of parts. | X | — | |
| Lock Strength | Applying 80 N force for the mating axis direction in state in fitted with applicable connector. | No unlocking, damage, cracks or looseness of parts. | X | — | |
| Wrenching Strength | Applying 25times of 30 N 1s for 2 axis direction on tip of plug case in state in fitted with applicable connector. | No damage, cracks or looseness of parts. | X | — | |
| ENVIRONMENTAL CHARACTERISTICS | | | | | |
| Rapid change of temperature | Subject mated specimens to 10 cycles between -55°C and 85°C with 30 minutes dwell at temp. extremes and 1 minute transition between temperatures. | 1) Voltage proof : 500 V DC applied for 1 min. Current leakage 2mA max. No flashover or breakdown. 2) Resistance: contact : 80 mΩ max. shield : 100 mΩ max. 3) Insulation resistance: 500 MΩ min. (at dry) 4) No damage, cracks or looseness of parts. | X | — | |
| Humidity / temperature cycling | low temperature 25 °C; high temperature 65 °C; cold sub-cycle - 10 °C; relative humidity 93 % duration 10 / each 24 h (IEC 60068-2-38, test Z / AD) | 1) Resistance: contact : 80 mΩ max. shield : 100 mΩ max. 2) Insulation resistance: 500 MΩ min. (at dry) 3) No damage, cracks or looseness of parts. | X | — | |
| Damp heat, steady state | Subject mated specimens to a relative humidity of 93 % at a temperature of 40°C during 21 days. | 1) Resistance: contact : 80 mΩ max. shield : 100 mΩ max. 2) Insulation resistance: 500 MΩ min. (at dry) 3) No damage, cracks or looseness of parts. | X | — | |
| Dry Heat | Subject to +85 ± 2 °C, 21 days. (mating applicable connector) | 1) Resistance: contact : 80 mΩ max. shield : 100 mΩ max. 2) Insulation resistance: 500 MΩ min. (at dry) 3) No damage, cracks or looseness of parts. | X | — | |
| Cold | Subject to -55 ± 3 °C, 10 days. (mating applicable connector) | 1) Resistance: contact : 80 mΩ max. shield : 100 mΩ max. 2) Insulation resistance: 500 MΩ min. (at dry) 3) No damage, cracks or looseness of parts. | X | — | |
| Corrosion Salt Mist | Subject to 5 % salt water, 35 ± 2 °C, 48h. (left under unmated condition.) | No heavy corrosion of contacts. | X | — | |
| Mixed flowing gas corrosion | Test temperature : +25±1 °C, Relative humidity : 75±3 % H ₂ S : 100±20 ppb, NO ₂ : 200±50 ppb Cl ₂ : 10±5 ppb, SO ₂ : 200±20 ppb Duration : 4 days, half mated half unmated (IEC 60512, method 4) | 1) Resistance: contact : 80 mΩ max. shield : 100 mΩ max. 2) No damage, cracks or looseness of parts. | X | — | |
| | | | | | |
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test | | DRAWING NO. | TELC-301076-00 | | |
| HRS | SPECIFICATION SHEET | | PART NO. | IX61-A-10P | |
| | HIROSE ELECTRIC CO., LTD. | | CODE NO | 251 |  2/3 |

SPECIFICATIONS

| ITEM | TEST METHOD | REQUIREMENTS | QT | AT |
|------------------------------|--|---|----|----|
| Solderability | Soldering point immersed in solder bath of $+235 \pm 5$ °C, 5 sec. (using type r flux) | Solder shall cover minimum of 95 % of The surface being immersed. | X | — |
| Resistance To Soldering Heat | A profile is shown in Fig-1, under 2 cycles. | No deformation or significant looseness of contacts. | X | — |




Fig – 1 Resistance to soldering heat
(temperature at top surface of connector)

Recommended profile refers to Fig – 2.
(temperature at SMT leads)




Fig – 2 Recommended reflow profile temperature

| | | | | |
|--|---------------------------|-------------|----------------|-------|
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test | | DRAWING NO. | TELC-301076-00 | |
| HRS | SPECIFICATION SHEET | PART NO. | IX61-A-10P | |
| | HIROSE ELECTRIC CO., LTD. | CODE NO | 251 | △ 3/3 |