



Pin Hole Layout
(Jack Bottom View)



RoHS
Compliant

SPECIFICATIONS:
 Contact Resistance : 30mΩ max
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstanding Voltage: AC 500V for one minute
 Remark: ▲: The Most Important Dimension

| | | | | | |
|-----|------------------|------------------|-----------|----------------|-------------|
| 5. | Insulator | PBT | 1 | Black Color | |
| 4. | Insulator | PBT | 1 | Green Color | |
| 3. | Pin | 0.25T Brass | 1 | Silver plated | |
| 6 | 2. | Mounting Bracket | 0.4T Iron | 1 | Tin Plating |
| 1. | Phone Jack Shell | 0.3T Brass | 1 | Nickel Plating | |
| NO. | Description | Material | Q'TY | Finish | |

HO CHIEN
www.hochien.com

| | | | | |
|------------|-----|------|------|---------|
| DATE | DWN | CHKD | APVD | MANAGER |
| 10.12.2010 | 李世強 | 陳加敏 | 張永 | 鄧國強 |

| | | | | |
|---|--|----------------------------|----------|--------------|
| PART NAME : PIN JACK | | PART NUMBER: SCP606UNS7T0G | | VERSION: 1.0 |
| TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED | | | UNIT: mm | SCALE: 1/1 |