




26/24 Rings

CMA Range 202-320

Barrel Inside Diameter .027"/.686 mm






Material: COPPER Thickness: .023"/.584 mm

Basic Dimensions					Non-Insulated	Insulated (Yellow Nylon)				
Stud Size	W In.	W mm	C In.	C mm		Funnel FIG	E In.	E mm	L In.	L mm
2	0.14	3.56	0.17	4.32	R4086	XR26336N	0.58	14.7	0.67	17.0
4	0.20	5.08	0.22	5.59	R4087	XR26337N	0.64	16.3	0.74	18.8
6	0.25	6.35	0.26	6.60	R4088	XR26338N	0.68	17.3	0.81	20.6
8	0.32	8.13	0.26	6.60	R4089	XR26339N	0.68	17.3	0.84	21.3
10	0.32	8.13	0.26	6.60	R4090	XR26340N	0.68	17.3	0.87	21.3
Hand Tool					H74	H7B & H53				

22/16* Rings

CMA Range 509-3260

Barrel Inside Diameter .059"/1.5 mm



Material: COPPER Thickness: .030"/.762 mm

Basic Dimensions					Non-Insulated				Insulated (Red Vinyl)				Insulated (Red Nylon)							
Stud Size	W In.	W mm	C In.	C mm	NIT	NIT Brazed	E In.	E mm	L In.	L mm	Insul. Dia. .160" / 4.06 mm				Insul. Dia. .146"/3.71 mm					
											Funnel FIT	E In.	E mm	L In.	L mm	Funnel FIG	E In.	E mm	L In.	L mm
2	.22	5.59	.16	4.06	R4103	R4103B	.44	11.17	.55	13.97	R4140F	.70	17.78	.81	20.57					
2	.22	5.59	.16	4.06	R4103S	R4103SB	.34	8.63	.45	11.43	R4140SF	.63	16.00	.74	18.80	XR1879SN	.63	16.00	.74	18.80
4	.22	5.59	.16	4.06		R4104B	.44	11.17	.55	13.97										
4	.22	5.59	.16	4.06	R4104S	R4104SB	.34	8.63	.45	11.43	R4141SF	.63	16.00	.74	18.80	XR1880SN	.63	16.00	.74	18.80
4	.28	7.11	.32	8.13	R4261S	R4261SB	.50	12.70	.64	16.25	R4265SF	.79	20.07	.93	23.62	XR1856SN	.79	20.07	.93	23.62
6	.22	5.59	.16	4.06	R4105	R4105B	.44	11.17	.55	13.97	R4142F	.70	17.78	.81	20.57					
6	.22	5.59	.16	4.06	R4105S	R4105SB	.34	8.63	.45	11.43	R4142SF	.63	16.00	.74	18.80	XR1881SN	.63	16.00	.74	18.80
6	.25	6.35	.32	8.13	R4110	R4110B	.59	14.98	.73	18.54	R4147F	.86	21.84	.98	24.89					
6	.25	6.35	.32	8.13	R4110S	R4110SB	.50	12.70	.62	15.74	R4147SF	.79	20.07	.91	23.11	XR1885SN	.79	20.07	.92	23.37
6	.28	7.11	.32	8.13	R4262	R4262B	.59	14.98	.73	18.54	R4266F	.86	21.84	1.00	25.40					
6	.28	7.11	.32	8.13	R4262S	R4262SB	.50	12.70	.64	16.25	R4266SF	.79	20.07	.93	23.62	XR1857SN	.79	20.07	.93	23.62
8	.22	5.59	.16	4.06	R4193	R4193B	.43	10.92	.55	13.97	R4206F	.70	17.78	.81	20.57					
8	.22	5.59	.16	4.06	R4193S	R4193SB	.33	8.38	.45	11.43	R4206SF	.63	16.00	.74	18.80	XR1882SN	.63	16.00	.74	18.80
8	.28	7.11	.32	8.13	R4263S	R4263SB	.50	12.70	.64	16.25	R4267SF	.79	20.07	.93	23.62	XR1858SN	.79	20.07	.93	23.62
8	.31	7.87	.32	8.13	R4111	R4111B	.60	15.24	.75	19.05	R4148F	.86	21.84	1.01	25.65					
8	.31	7.87	.32	8.13	R4111S	R4111SB	.50	12.70	.65	16.51	R4148SF	.79	20.07	.94	23.88	XR1890SN	.79	20.07	.94	23.88
10	.28	7.11	.32	8.13	R4264	R4264B	.59	14.98	.73	18.54	R4268F	.86	21.84	1.00	25.40					
10	.28	7.11	.32	8.13	R4264S	R4264SB	.50	12.70	.64	16.25	R4268SF	.79	20.07	.93	23.62	XR1859SN	.79	20.07	.93	23.62
10	.31	7.87	.32	8.13	R4112	R4112B	.60	15.24	.75	19.05	R4149F	.86	21.84	1.01	25.65					
10	.31	7.87	.32	8.13	R4112S	R4112SB	.50	12.70	.65	16.51	R4149SF	.79	20.07	.94	23.88	XR1891SN	.79	20.07	.94	23.88
1/4	.47	11.94	.44	11.18	R4113	R4113B	.71	18.03	.94	23.87	R4150F	.97	24.64	1.21	30.73					
1/4	.47	11.94	.44	11.18	R4113S	R4113SB	.61	15.49	.85	21.59	R4150SF	.90	22.86	1.14	28.96	XR1894SN	.90	22.86	1.14	28.96
5/16	.47	11.94	.44	11.18	R4114	R4114B	.71	18.03	.94	23.87	R4151F	.97	24.64	1.21	30.73					
5/16	.47	11.94	.44	11.18	R4114S	R4114SB	.61	15.49	.85	21.59	R4151SF	.90	22.86	1.14	28.96	XR1895SN	.90	22.86	1.14	28.96
3/8	.53	13.46	.44	11.18	R4115	R4115B	.71	18.03	.97	24.63	R4152F	.97	24.64	1.24	31.50					
3/8	.53	13.46	.44	11.18	R4115S	R4115SB	.61	15.49	.88	22.35	R4152SF	.90	22.86	1.17	29.72	XR1896SN	.89	22.61	1.16	29.46
Hand Tool					H4A	H4A	H7B & H53**				H7B & H53									



* 22-16 Rings are marked 22-18 in accordance with AS7928

** H53 for short barrel, H53L for long barrel

