

Applications

- Industrial
- Electronic instruments
- Automotive/marine equipment
- Power tools
- Home appliances
- Emergency lighting
- Vending machines

Pull-Chain Switch

Product Features

- Plastic body and nipple
- Nipple 3/8" – UNS 27 x 5/16" long
- Aluminum knurled nut, brass or nickel finish

Variable-Speed Pull-Chain Switch

Product Features

- Plastic body and nipple
- Brass knurled nut
- Nipple 3/8" – UNS 27 x 3/8" long

All-Angle Pull-Chain

Product Features

- Plastic body and metal nipple
- Nipple 15/32" – UNS 32
- Steel lockout

Pull-Chain and Variable-Speed Pull-Chain Switches and All-Angle Pull-Chain Switches Compliances

- 
- 

Snap-In Rocker Switches

Product Features

- Nylon body and rocker
- Polycarbonate rocker (#6437)
- Contacts – silver-plated copper-alloy
- .250 quick connect tabs
- Fits cutout 17/32" x 1-1/8"

Snap in Rocker Switches Compliances

- 
- 



6401, 6354



6402, 6355



6403, 6404



6405



6436



6437

ORDERING INFORMATION - DIMENSIONS

PULL-CHAIN SWITCHES – FOR LAMPS AND CEILING FIXTURES				
CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6401	SPST, on-off 6" leads, brass finish Carded	6 amp, 125V AC 3 amp, 250V AC 6 amp, 125V L	5	
6354	SPST, on-off 6" leads, brass finish Bulk Poly Bag	6 amp, 125V AC 3 amp, 250V AC 6 amp, 125V L	25	
6402	SPST, on-off 6" leads, nickel finish Carded	6 amp, 125V AC 3 amp, 250V AC 6 amp, 125V L	5	
6355	SPST, on-off 6" leads, nickel finish Bulk Poly Bag	6 amp, 125V AC 3 amp, 250V AC 6 amp, 125V L	25	

VARIABLE-SPEED PULL-CHAIN SWITCHES – FOR CEILING FANS				
CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6403	2-speed, off-on-on Stab connections, brass finish Carded	6 amp, 125V AC 3 amp, 250V AC 6 amp, 125V L	5	
6404	3-speed, off-on-on-on, Stab connections, brass finish, Carded	6 amp, 125V AC 3 amp, 250V AC	5	

ALL-ANGLE PULL-CHAIN – FOR CEILING FIXTURES				
CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6405	All angle, on-off 3" leads, SPST, Carded	6 amp, 125V AC 3 amp, 250V AC	5	

SNAP-IN ROCKER SWITCHES – FOR RANGE HOOD AND APPLIANCES				
CATALOG NUMBER	DESCRIPTION	ELECTRICAL RATINGS	STD. PKG.	UPC BAR CODE
6436	Rocker, SPST, on-off Opening 17/32" x 1-1/8" Carded	16 amp, 250V AC 1 HP, 250V AC 1/2 HP, 125V AC	5	
6437	Lighted rocker SPST, on-off Opening 17/32" x 1-1/8" Carded	110V Lamp 16 amp, 250V AC 15 amp, 1 HP, 250V AC 1/2 HP, 125V AC	5	