## INDUSTRIAL CONTROL COMMUNICATIONS, INC.

## PBDP-1000 Multiprotocol Profibus DP-V1 Gateway

## Flexible, Powerful and Easy-to-Use Profibus DP-V1 Gateway

The PBDP-1000 is a user-configurable multiprotocol Profibus DP-V1 / RS-485 communications gateway, which allows seamless bridging between Profibus networks and various popular RS-485 based industrial and commercial communication networks. As a member of the Millennium Series line of communication gateways, the PBDP-1000 is able to leverage the common form factor, configuration and usage experience available to all of these products. Using the Microsoft Windows®-based *ICC Configuration Studio*, users can perform the following tasks:




- Configure protocols, network characteristics, and client/server object definitions
- Graphically interact with the internal database in real-time
- Automatically update device firmware
- Define autonomous internal elements such as database logic and object failsafe values
- Capture, display and save serial network traffic with microsecond-precision timestamps

The PBDP-1000 incorporates a variety of leading-edge automation technology elements, such as:

- Power can be supplied via the USB cable (for configuration at a workstation) or as a 7-24VDC input on the main terminal block
- Profibus DP-V1 support for both cyclic and acyclic (class 1 and class 2) communications
- Acyclic access to entire internal database as 8-bit, 16-bit or 32-bit data types
- Controlled by a powerful 32-bit processor
- User-configurable network timeout behaviors
- USB connectivity with virtual COM port support
- 2-wire / 4-wire RS-485 network supports baud rates up to 115.2kbaud
- Desktop, panel/wall and DIN-rail mountable (all hardware included)
- Supports all Profibus baud rates
- Supports up to 368 bytes of combined Profibus input and output cyclic data

Supported networks/protocols currently include:

- Profibus DP-V1 (slave)
- Modbus RTU (master, slave & sniffer)
- BACnet MS/TP (client & server)
- Johnson Controls Metasys® N2 (master & slave)
- Toshiba ASD protocol (master)
- Sullair Supervisor protocol (master)



- M-Bus (master)
- Siemens FLN (master & slave)
- For a complete list of supported drivers, refer to the "Millennium Series Supported Drivers List"



1600 Aspen Commons, Suite 210 Middleton, WI 53562 USA

Phone: (608) 831-1255 Fax: (608) 831-2045 http://www.iccdesigns.com

For more information about this and other industrial & commercial communication interface products, visit us online at http://www.iccdesigns.com.



