



■ SPECIFICATIONS

- Voltage Rating : 100 V AC/DC
- Current Rating : 1A AC/DC
- Withstanding Voltage : 500V AC/minute
- Insulation Resistance : 500MΩ min
- Temperature Range : - 25°C to + 85°C
- Contact Resistance : 20mΩ max

■ WAFER

- Poles : 2 - 30
- Material : Contact : Phos. Bronze, Tin Plated
Base : Nylon 9T UL94V-0
- Q' ty : 1,000 pcs./Tape & Reel

HOW TO ORDER:

W 1 2 6 - X X 1 0 - 0 0 0 0 - Z

OF POSITIONS:

2, 3, 4, 5, 6, 7, 8, 9, 10,
12, 20, 25, 30

**RoHS
COMPLIANT**

HOUSING & TERMINATION TYPE:

1 - RIGHT ANGLE HEADER, SURFACE MOUNT

Circuits	Dimensions (mm)		
	A	B	C
2	1.25	7.45	-----
3	2.50	8.70	-----
4	3.75	9.95	-----
5	5.00	11.20	10.20
6	6.25	12.45	11.45
7	7.50	13.70	12.70
8	8.75	14.95	13.95
9	10.00	16.20	15.20
10	11.25	17.45	16.45
12	13.75	19.95	18.95
20	23.75	29.95	28.95
25	30.00	36.20	35.20
30	36.25	42.45	41.45

Rev	Drawn	Checked	Approved	Date
0 Issued	MDH	S.M.	S.M.	09/16/04
A Revised for RoHS Compliance	B.S.	S.M.	S.M.	08/01/08

SMP TECHNOLOGY, INC.

1.25mm Pitch Surface Mount Header (Hirose DF14 Style)

2 - 30 Positions

TOL. DEC. .X +/- .XX +/- .XXX +/- ANGLE +/- UNIT: mm

P/N : W126-XX10-000-Z

Pg: 1