



No. of Circuits	Dimensions	
	A	B
2	2.00	6.00
3	4.00	8.00
4	6.00	10.00
5	8.00	12.00
6	10.00	14.00
7	12.00	16.00
8	14.00	18.00
9	16.00	20.00
10	18.00	22.00
11	20.00	24.00
12	22.00	26.00
13	24.00	28.00
14	26.00	30.00
15	28.00	32.00

Accept Contact P/N: W032-0010-201-Z

**ELECTRICAL:**

CURRENT RATING: 1 A AC,DC  
 VOLTAGE RATING: 100V AC,DC  
 TEMPERATURE RANGE: -25°C TO +85°C  
 CONTACT RESISTANCE: 20mΩ (Max.)  
 INSULATOR RESISTANCE: 1000 MΩ Min.  
 WITHSTANDING VOLTAGE: 800V AC/MINUTE

**MATERIAL:**

NYLON 66,UL94V-0

**HOW TO ORDER:**

W 0 3 2 - X X 1 0 - 1 0 0 - Z

**# OF POSITIONS:**

2 thru 15

**RoHS  
COMPLIANT**

Rev	Drawn	Checked	Approved	Date
0	B.S.	S.M.	S.M.	3/21/07

**SMP TECHNOLOGY, INC.**

SCALE

Contact Housing, 2.00mm Pitch, AMP CT Type

TOL. DEC. .X +/- 0.2 .XX +/- .XXX +/- ANGLE +/- UNIT: mm

P/N: W032-XX10-100-Z