

LED SPECIAL Type




OEM / ODM Are Welcome

LED Special Type

LED 特殊機型

LED Module

光源模塊

LED - Module LED - 光源模塊									
Size (mm)	φ43 x 7.5	φ99 x 7.5	φ99 x 7.5	φ99 x 7.5	φ140 x 7.5	φ146 x 4.0	φ146 x 4.0	φ200 x 4.0	φ200 x 4.0
VDC (V)	10.5	14	21	31.5	35	35	35	31.5	35
Watt. (W)	3.5	4.6	7	10	23	15.75	31.5	47	63
mA	330	330	330	330	660	450	900	1,500	1,800
lm	270	360	540	810	1,800	1,050	2,100	3,150	4,200
LED (PCS)	1W x 3	1W x 4	1W x 6	1W x 9	1W x 20	0.5W x 30	1W x 30	1W x 45	1W x 60

LED Driver (Isolation Structure)

LED 驅動器 (隔離式)



(A)

(B)

(C)

(D)

(E)

(F)

(G)

(H)

Input Watt. 輸入瓦數 (W)	Input Vol. 輸入電壓 (V)	Output Current 輸出電流 (A)	Output Vol. 輸出電壓 (VDC)	P.F. 功率因數 (%)	Effi 轉換效率 (%)	Constant Vol. 定電壓 (VDC)	Constant Current 定電流 (A)	L x W x H 長 x 寬 x 高 (mm)	Dimension 外觀尺寸
9	100 ~ 242	0.7	12	> 0.50	70		●	60 x 40 x 27	A
30 / 15	100 ~ 242	0.9 / 0.45	33	> 0.95	75		●	136 x 88 x 40	D
50 / 30 / 20	100 ~ 242	1.5 / 0.9 / 0.6	33	> 0.90	78		●	105 x 105 x 34	B
60	100 ~ 242	1.7	36	> 0.95	83	●		140 x 89 x 35	C
20	100 ~ 242	1.1	18	> 0.90	75		●	205 x 45 x 33	F
100 / 70	100 ~ 242	2.6 / 1.8	39	> 0.95	85		●	140 x 109 x 46	E
120	100 ~ 242	3.05	39	> 0.95	86		●	180 x 110 x 46	G
150	100 ~ 242	3.85	39	> 0.95	86		●	180 x 110 x 46	G
180	100 ~ 242	7.50	24	> 0.95	88	●		225 x 71 x 48	H

Applications : Explosion - proof lighting, street lighting, table lighting, wall lighting and so on.

適用：防爆燈具、路燈、檯燈、投射燈 等等。

LED Driver (Non Isolation Structure)

LED 驅動器 (非隔離式)



Input Watt. 輸入瓦數 (W)	Input Vol. 輸入電壓 (V)	Output Current 輸出電流 (A)	Output Vol. 輸出電壓 (VDC)	P.F. 功率因數 (%)	Effi 轉換效率 (%)	Constant Vol. 定電壓 (VDC)	Constant Current 定電流 (A)	L x W x H 長 x 寬 x 高 (mm)
10	100 ~ 242	0.2	51	> 0.50	75		●	74.5 x 22 x 15
20 / 10	100 ~ 242	0.4 / 0.2	51	> 0.85	90		●	275 x 17 x 11
25	100 ~ 242	0.49	51	> 0.90	90		●	290 x 20 x 13.5
30	100 ~ 242	0.59	51	> 0.92	90		●	290 x 20 x 13.5
40	100 ~ 242	0.78	51	> 0.92	90		●	290 x 20 x 13.5

Applications : LED tube, long narrow LED lighting, LED aquarium lighting and so on.

適用：LED 燈管、條型 LED 燈具、LED 水族箱 等等。

LED Current Controller (DC to DC)

LED 分流器 (DC to DC)




Input Watt. 輸入瓦數 (W)	Input Vol. 輸入電壓 (VDC)	Output LED Current Controller LED 輸出定電流控制			L x W x H 長 x 寬 x 高 (mm)
		Output Vol. 輸出電壓	Watt. 輸出瓦數	mA / Set	
60	36	33	10	330 / 6	155 x 45 x 19
140	24	21	35	1,650 / 4	130 x 58 x 20

Applications : Street lighting, solar lighting and so on.

適用：路燈分流、高天井燈 等等。

Solar LED Driver (DC to DC)

LED 太陽能用直流驅動器 (DC to DC)



Input Watt. 輸入瓦數 (W)	Input Vol. 輸入電壓 (VDC)	Output LED Current Controller LED 輸出定電流控制			L x W x H 長 x 寬 x 高 (mm)
		Output Vol. 輸出電壓	Watt. 輸出瓦數	mA / Set	
20	18 ~ 36	33	20	600	105 x 105 x 15
17	29 ~ 34	24	17	700	61 x 31 x 21.5

Applications : Solar Street lighting, solar lighting and so on.

適用：太陽能路燈 等等。

Protection : Short Circuit Protection, Battery End of Power Protection, Over Temperature Protection.

特點：輸出短路保護、電池截止電壓保護、過溫保護。

※1. Open Frame without enclosure. (Size Could Be Negotiated) 特殊機型無外殼隨客戶設計。

※2. Other Series subject to be enquiry. 其他規格可向公司洽詢。