


THIS IS A 16 PORT TRANSCEIVER TEST SYSTEM.  
 IT IS FULL FAN-OUT.  
 EVERY PORT CONNECTS TO EVERY OTHER PORT VIA 120 INTERNAL RF PATHS.  
 IT HAS A PROGRAMMABLE ATTENUATOR ON EVERY RF PATH (120 TOTAL ATTENUATORS).

| REV | ECN    | DATE     | BY  | APPR |   |   |
|-----|--------|----------|-----|------|---|---|
| -   | ISSUED | 10-21-10 | BZ  | TRS  |  <b>JFW INDUSTRIES, INC.</b><br>www.jfwindustries.com PH: 317-887-1340 |   |
| A   | 20205  | 6-13-11  | DTS | TRS  |   |   |
| B   | 26712  | 6-13-16  | DTS | TRS  |   |   |
|     |        |          |     |      | MATERIAL  | PROPRIETARY INFORMATION                                 |
|     |        |          |     |      | FINISH  | ALL SURFACES ARE TO BE FREE OF BURRS, PITS, & SCRATCHES |
|     |        |          |     |      | MODEL   | TOLERANCES  |
|     |        |          |     |      | 50PMA-XXX   | .XX±.010 .XXX±.005 XX'±.5'                              |
|     |        |          |     |      | DESCRIPTION   | DWG #   |
|     |        |          |     |      | 16 PORT TRANSCEIVER TEST SYSTEM   | 092-6753  |