



MODEL ULTS TUBE-N-TUBE UNIGAUGE™



- Only wetted part is one-piece, clear FEP Teflon®
- Approved by the Factory Mutual System (150°F max)
- Max length for FM approved models per specification below
- Unobstructed visibility
- Maintenance free
- Flared FEP Teflon® forms flange gasket
- Designed for cryogenic or hot process applications
- Inner sight tube is protected and isolated
- Transparent insulation reduces heat loss, eliminates many heat tracing requirements
- Excellent for corrosive, viscous, or sanitary service
- Rated up to 285 psig (ANSI 150)
- Polycarbonate sleeves rated up to 100°F
- Optional 316 SS
- ANSI Class 300 lb flanges are available
- Custom designs available; consult factory

Standard Construction

- FEP Teflon® inner sight tube, flared
- PTFE Teflon® SuperSeal inserts
- Polycarbonate or borosilicate sight tube sleeve
- Epoxy-coated carbon steel shield and flanges
- ANSI Class 150-lb flanges




Model ULSS Specifications





Sight tube material	Sight tube size, in.	Outer tube material	Outer tube size, inches	Sleeve tube material	Sleeve tube size, in.	Gauge rating, psig	Sleeve tube size, in.	Sleeve tube size, in.
FP	1.00	LX	2.25	LX	1.25	150	1.50	96
FP	1.00	OG	2.00	LX	1.25	150	1.50	59
FP	1.00	LX	2.25	PI	1.00	150	1.50	119
FP	1.00	LX	2.75	LX	1.25	150	2.00	96
FP	1.00	OG	2.75	LX	1.25	150	2.00	59
FP	1.00	LX	2.75	PI	1.00	150	2.00	96
FP	1.00	OG	2.75	PI	1.00	150	2.00	59
FP	1.25	LX	2.75	HW	1.50	285 ¹	2.00	48
FP	1.25	OG	2.75	HW	1.50	285 ¹	2.00	48
FP	1.50	LX	2.75	LX	1.75	135	2.00	96
FP	1.50	OG	2.75	LX	1.75	135	2.00	59
FP	1.50	LX	2.75	PI	1.50	135	2.00	96
FP	1.50	OG	2.75	PI	1.50	135	2.00	59
FP	1.63	LX	3.00	HW	2.00	285 ¹	3.00	59
FP	1.63	OG	4.00	HW	2.00	285 ¹	3.00	59
FP	2.00	LX	4.00	LX	2.25	115	3.00	96
FP	2.00	OG	4.00	LX	2.25	115	3.00	59
FP	2.00	LX	4.00	PI	2.00	115	3.00	96
FP	2.00	OG	4.00	PI	2.00	115	3.00	59

FP = FEP Teflon® PI = Standard Borosilicate HW = Heavywall Borosilicate OG = Outer Borosilicate LX = Polycarbonate
Note: (1) Actual flange pressure rating may be less based on material selected.



GAUGE-TO-VESSEL CONNECTIONS



				
TC	FC	TV	FV	LC
Gauge Connectors		Gauge Connector with Ball-n-ball valves		PTFE Teflon®-lined Gauge Connector
- Threaded 1/2 to 1 in. NPT (TC) - Flanged 1/2 to 2 in. (FC) - Carbon steel, 316 SS, or CPVC - Socket weld or weld neck flanges are available		- Threaded 1/2 to 1 in. NPT (TC) - Flanged 1/2 to 2 in. (FC) - Carbon steel, 316 SS, or CPVC - Socket weld or weld neck flanges are available		- Flanged 3/4, 1, 1-1/2, 2 in. 150 or 300 lb. ANSI - Carbon steel 316 SS

GAUGE ACCESSORIES


Blind Flanges

- Same size as gauge flange
- Captures connector with gasket and hardware
- Vent and drain sizes: 1/4 to 1 inch FNPT
- Carbon steel, 316 SS, or CPVC



Lined Reducing Flanges

- PTFE Teflon®-lined
- Sizes up to 10 in. x 8 in.
- Used in place of gauge connectors for non-standard installations



Calibration Scales

- Polycarbonate or 316 SS
- Inches/feet, total inches, or metric
- Custom-calibrated sight tubing available, consult factory



Explosion-Proof Illuminators

- 120-VAC, 56-watt, 3000-hour
- Class 1, Division 1, B, C, D, E
- Requires one lamp per 6 ft. of visual length

GAUGE AND CONNECTOR PART NUMBERS

Use the spaces below to generate the model number for your gauges. Codes for materials and diameters are from the chart below.

Overall length (L) inches	Gauge model	Sight tube material	Sight tube size	Shield material	Gauge flange size	Outer tube material	Outer tube size	Sleeve tube material	Sleeve tube material	Connector type	Connector material	Gauge flange size	Connection size
	ULTS	FP											

☐ Calibrated Scale: Polycarbonate ___ 316 SS ___ Sight Glass ___
Feet/Inches ___ Total Inches ___ Metric ___ Other ___

☐ Level floats: Orange PP ___ Red Teflon® ___

☐ Explosive-proof illuminator

☐ Sight tube redlining

☐ Vent and drain valves: Carbon steel ___ 316 SS ___ CPVC ___

☐ PTFE-lined reducing flanges: Size ___ x ___

☐ Internal heat tracing

Teflon is a registered trademark of E.I. DuPont

Sight tube material
FEP Teflon®

Sleeve tube material
Standard Borosilicate
Heavywall Borosilicate
Polycarbonate (100°F max)

Outer tube material
Borosilicate
Polycarbonate (100°F max)

Shield/Flange Material
Carbon Steel
316 SS

Code
FP

Code
PI
HW
LX

Code
OG
LX

Code
CS
S6

Connector Material
Carbon Steel
316SS
CPVC

Size, Inches	Code
1.00	10
1.25	12
1.50	15
1.62	16
1.75	17
2.00	20
2.25	22
2.75	27
3.00	30
4.00	40