MODEL LLT-IOOO LIDAR LEVEL TRANSMITTER



Description

Jogler's **LIDAR Level Transmitter** is a non-contact, laser based instrument that measures the level in silos, tanks, hoppers, chutes and bunkers. With long measuring range, high accuracy and a narrow beam, the **LLT-1000** can be used in many different applications to measure to different types of surface. The 4...20 mA and relay interfaces provide linear and switchpoint controls while the onboard USB interface provides access to comprehensive, user-friendly configuration settings. With an optional, visible aiming laser and numerous mounting flanges, the **LLT-1000** is an easy to use, state of the art, level and position sensing solution.

Technology

The **LLT-1000** measures distance using time-of-flight, laser technology. This fast and accurate measuring principle offers numerous advantages over other methods. The narrow beam makes it easy to aim directly at the most critical point in the vessel; the long range permits unlimited stand-off distances when measuring into aggressive environments; the laser can measure through protective windows and sight glasses; the accuracy is not affected by atmospheric temperature or humidity; the high signal-to-noise ratio gives clean, reliable signals under any lighting conditions and when measuring to any color or granularity of surface.

Standard Features

- Non-contact measurement of level or distance
- Narrow beam and long range for accurate targeting
- Local USB programmability allows for easy parameter changes
- Visible aiming laser (optional)
- Dual compartment housing
- Numerous mounting options
- General Purpose (FM and CSA pending)

Disclaimer

Information found in this document is used entirely at the reader's own risk and whilst every effort has been made to ensure its validity neither Jogler LLC nor its representatives make any warranties with respect the accuracy of the information contained herein.



SPECIFICATIONS

Performance

Range	2 180 ft (white), 2 100 ft (black), 2 330 ft (reflector)
Accuracy	+/- 0.5 inches (typical on white surface)
Repeatability	0.1% of full span
Linearity	0.1% of full span
Refresh rate	8 readings per second
Initiation	5.00 seconds
Damping	0.00 to 10.00 @ 0.01 seconds

Electrical

Input	1432 V DC (24 V DC nominal)
Output	420 mA NAMUR compliant self-powered & non-isolated 2 x Relays (N/O, N/C), 250 V at 3 A
Resistance	600 Ohms (max) @ 24 V DC
Power	2.4 watts (24 V DC x 100 mA)
Error signal	3.60 mA (low) or 22.0 mA (high)
Interface	Mini-USB
Software	Jogler Terminal software
Connection	0.5 inch NPT

Ratings

MAWP	1 bar
Ambient temp.	-4° to +140° F (-20° to +60° C)
Area rating	Class I, Division 2, Groups A, B, C, D Class II and III Groups E, F, G T4
Enclosure	Powder Coated, Aluminum, IP 67

ORDERING INFORMATION

Model Number: LLT-1000/a

/A Visible aiming laser pointer

S	Standard instrument without visible aiming laser pointer
Р	Instrument with visible aiming laser pointer





Units in mm (inch)

PC setup

- Install the latest revision of Jogler Terminal software and open.
- Connect the LLT-1000 to a PC using a USB 2.0 B male to mini B male cable. This provides both power and communication for the unit.
- Click the Jogler Terminal software's "Connect" icon to open a communications port. The distance measurements should

1.79 m mA 100 %	Distance 420 mA output Signal strength
1.79 m mA 100 %	
1.79 m mA 100 %	

begin to scroll in the Terminal window as follows:

 If an automatic connection is not created, click the "Laser" icon and select the appropriate USB port and 115200 baud rate.

 **** Settings *** a: Hide 4-20 mA settings b: 4 mA distance setting 25.00 m c: 20 mA distance setting 0.60 m d: 4-20 mA fail safe current >21.0 mA e: 4-20 mA test 19.22 mA 	Enter the distance that corresponds to the 4 mA output value. Enter the distance that corresponds to the 20 mA output value. Enter the failsafe condition of the 420 mA range for alarm indications. Test the 420 mA output
f: Hide relay settings g: Relay A switch point 1 1.00 m h: Relay A switch point 2 2.00 m i: Relay A mode near => closed far => open j: Relay B switch point 1 1.00 m k: Relay B switch point 2 2.00 m l: Relay B mode near => closed far => open m: Relay test A:open B:open	Enter the first distance at which relay A activates. Enter the second distance at which relay A activates. Enter the polarity for relay A Enter the first distance at which relay B activates. Enter the second distance at which relay B activates. Enter the polarity for relay B Test the relays
n: Hide system settings o: Measuring units meters p: Zero distance offset 0.00 m q: Lost signal timeout 4.0 sec r: Distance result Filtered s: Maximum filling rate 100.00 m/min t: Visible aimer ON u: Aimer stops after 2 min	Enter the required measuring units Enter the zero datum trim Enter the lost signal hold time delay Select to output results as raw or filtered Enter the maximum filling rate Select the visible aiming laser ON continuously, or OFF Enter the visible aiming laser time out duration

- To access the configuration menu of the LLT-1000, press the < space > key on the keyboard.

- To restart measurements, press the < space > key.
- To save a copy of the current screen data, click the "Save" icon.
- If you wish to start recording data, click the "Log" icon.
- To clear the screen of measurement data, click the "Clear" icon.
- Once you have configured the LLT-1000, click the "Disconnect" icon and disconnect the mini-USB cable from the unit.





Measuring laser of the LLT-1000/S and LLT-1000/P

The LLT-1000/* is a laser rangefinder that emits invisible ionizing laser radiation from its measuring laser. The unit is classified as Class 1M (EN/IEC 60825-1 2008) during all procedures of operation. This classification indicates that the laser beam is safe to look at with the unaided eye, but must not be viewed directly using binoculars or other optical devices at a distance of less than 14.53 meters.

Specification	Value
Laser emission wavelength	905 nm
Maximum average radiant power	15 W
Pulse width (half power points)	20 x 10-9
Beam divergence, of laser before optics	Horiz 15° Vert 30°
Beam diameter at laser aperture	21.8 mm
Laser output	Pulsed
Pulse energy (J) of single pulse	300 x 10-9 J
Pulse repetition rate	36 kHz
Angle of subtense of beam	<1.5 mrad
Beam divergence	9.77 mrad
Laser source size (X x Y)	10 x 200 µm
Nominal Ocular Hazard Distance and Area	<15 m

Aiming laser of the LLT-1000/P

The LLT-1000/P contains an aiming laser that emits visible laser radiation. The unit is classified as Class 2 (EN/IEC 60825-1 2008) during the following modes of operation:

- During commissioning mode, the visible aiming laser has an automatic time-out of 1 minute;
 - During running mode, the visible aiming laser can be set to:
 - Ash continuously with a 25% duty-cycle;
 - Ash with a 25% duty-cycle and time-out after a preset duration (user selectable from 1 to 10 minutes).

Value

This classification indicates that the laser beam must not be stared at with the unaided eye.

Specification

-	
Laser emission wavelength	670 nm
Maximum radiant power	0.0008 W
Laser output	CW



Service and maintenance

The laser eye safety ratings depend on the mechanical integrity of the optics and electronics. The LLT-1000 has no user serviceable components. Repair and service must only be carried out by the manufacturer or a factory-trained technician. No regular maintenance is required for the LLT-1000 but if the lenses start to collect dust then they may be wiped with suitable lens cleaning materials. Ensure that the LLT-1000 is switched OFF before looking into the lenses.

