





銅スリーブ入絶縁付角先開形端子(ストレート形)























































































A形

B形




UL E42024 LR20812

形番		規格	寸法(mm)							標準色	適用電線範囲	適用圧着工具			1箱 入数 (個)
			d2	B	L	F	ℓ	φD	T		燃線(mm²)	手動	空気圧式	油圧式	
A形	VD1.25-B3A	 	3.2	5.8	20.6	6.3	9.6	3.5	0.8	赤	0.25~1.65 (0.3 (AWG#22) 0.5 (AWG#20) 0.75 (AWG#18) 0.9 1.25 (AWG#16)	YNT-2216	YA-1 YA-2 YAT-1A YAT-2A YAD-1A YAD-2A YA-4 YAT-4A YAD-4A	BCT-0514L	1,000
	VD1.25-YS3A	 		6.4	20.2										
	VD1.25-S3A	 	3.7	7.2	20.6										
	VD1.25-N3A	 		6.2	20.6										
	VD1.25-YS4A	 	4.3	6.4	20.2	7.0									
	VD1.25-S4A	 		7.2	20.6										
	VD1.25-4A	 		8.5	20.6										
	VD1.25-5A	 	5.3	9.5											
	VD1.25-6A	 	6.4	12.0	26.8	11.0									
	VD2-N3A	 	3.2	5.9	20.6	6.3	9.6	4.1	0.8	青	1.04~2.63 (1.25 (AWG#16) 2.0 (AWG#14)	YNT-1614	YA-1 YA-2 YAT-1A YAT-2A YAD-1A YAD-2A YA-4 YAT-4A YAD-4A	BCT-0514L	1,000
	VD2-YS3A	 	3.7	6.4	20.2										
	VD2-S3A	 		7.2	20.8	6.5									
	VD2-YS4A	 	4.3	6.4	20.2	6.3									
	VD2-YM4A	 		6.8	20.2	6.3									
	VD2-S4A	 		7.2	20.8	6.5									
	VD2-4A	 		8.5	21.6	7.3									
	VD2-5A	 	5.3	9.5											
	VD2-6A	 	6.4	12.0	26.8	11.0									
	VD5.5-S3A	 	3.7	7.2	26.7	7.5	14.0	5.7	1.0	黄	2.63~6.64 (3.5 (AWG#12) 5.5 (AWG#10)	YNT-1210S	YA-4 YAT-4A YAD-4A	BCT-0514L	500
	VD5.5-3A	 		9.5											
	VD5.5-S4A	 	4.3	8.5											
	VD5.5-4A	 		9.5											
	VD5.5-5A	 	5.3												
	VD5.5-6A	 	6.4	13.5	32.7	12.2									
B形	VD1.25-S3B	 	3.7	7.5	17.9	5.1	9.6	3.5	0.8	赤	0.25~1.65 (0.3 (AWG#22) 0.5 (AWG#20) 0.75 (AWG#18) 0.9 1.25 (AWG#16)	YNT-2216	YA-1,YA-2 YAT-1A,YAT-2A YAD-1A,YAD-2A YA-4 YAT-4A YAD-4A	BCT-0514L	1,000
	VD1.25-3B	 		8.5	22.3	7.2									
	VD1.25-S4B	 	4.3	7.5	17.9	5.1									
	VD1.25-4B	 		8.5	23.3	7.2									
	VD1.25-5B	 	5.3												
	VD1.25-6B	 	6.4	13.5	28.8	11.7									500
	VD2-T3B	 	3.7	7.5	18.3	5.2	9.6	4.1	0.8	青	1.04~2.63 (1.25 (AWG#16) 2.0 (AWG#14)	YNT-1614	YA-1,YA-2 YAT-1A,YAT-2A YAD-1A,YAD-2A YA-4 YAT-4A YAD-4A	BCT-0514L	1,000
	VD2-3B	 		8.5	21.8	7.2									
	VD2-T4B	 	4.3	7.5	18.3	5.2									
	VD2-4B	 		8.5	21.8	7.3									
	VD2-5B	 	5.3												
	VD2-6B	 	6.4	13.5	28.8	11.7									500
	VD5.5-S3B	 	3.7	7.6	25.2	6.2	14.0	5.7	1.0	黄	2.63~6.64 (3.5 (AWG#12) 5.5 (AWG#10)	YNT-1210S	YA-4 YAT-4A YAD-4A	BCT-0514L	500
	VD5.5-3B	 		8.5	26.7	7.5									
	VD5.5-S4B	 	4.3	7.6	25.2	6.2									
	VD5.5-4B	 		8.5	26.7	7.5									
	VD5.5-5B	 	5.3												
	VD5.5-6B	 	6.4	13.5	33.7	12.2									250


注1) 丸先開形端子(X形)、丸横開形端子(Y形)仕様も製作できます。詳細は弊社までお問い合わせください。

注2) 本製品の中には多少納期を要するものもあります。




絶縁被覆付圧着端子

■銅スリーブ入絶縁付角先開形端子(F形)



A形





















































































B形



E42024



LR20812

形 番		規 格	寸 法(mm)							標準色	適用電線範囲	適用圧着工具			1箱 入数 (個)
			d2	B	L	F	ℓ	φD	T		燃線(mm ²)	手 動	空 気 圧 式	油 圧 式	
A形	FVD1.25-B3A	 	3.2	5.8	20.6	6.3	9.6	4.0	0.8	赤	0.25~1.65 { 0.3 (AWG#22) 0.5 (AWG#20) 0.75 (AWG#18) 0.9 1.25 (AWG#16) }	YNT-2216	YA-1 YA-2 YAT-1A YAT-2A YAD-1A YAD-2A YA-4 YAT-4A YAD-4A	BCT-0514L	1,000
	FVD1.25-YS3A	 		6.4	20.2										
	FVD1.25-S3A	 	3.7	7.2	20.6										
	FVD1.25-N3A	 		6.2											
	FVD1.25-YS4A	 		6.4	20.2										
	FVD1.25-S4A	 	4.3	7.2	20.6	7.0									
	FVD1.25-4A	 		8.5											
	FVD1.25-5A	 	5.3	9.5											
	FVD1.25-6A	 	6.4	12.0	26.8	11.0									
	FVD2-N3A	 	3.2	5.9	20.6	6.3	9.6	4.7	0.8	青	1.04~2.63 { 1.25 (AWG#16) 2.0 (AWG#14) }	YNT-1614	YA-1 YA-2 YAT-1A YAT-2A YAD-1A YAD-2A YA-4 YAT-4A YAD-4A	BCT-0514L	1,000
FVD2-YS3A	 	3.7	6.4	20.2											
FVD2-S3A	 		7.2	20.8	6.5										
FVD2-YS4A	 	4.3	6.4	20.2	6.3										
FVD2-YM4A	 		6.8	20.8	6.5										
FVD2-S4A	 		7.2	20.8	6.5										
FVD2-4A	 		8.5	21.6	7.3										
FVD2-5A	 	5.3	9.5												
FVD2-6A	 	6.4	12.0	26.8	11.0										
FVD5.5-S3A	 	3.7	7.2	26.7	7.5	14.0	6.5	1.0	黄	2.63~6.64 { 3.5 (AWG#12) 5.5 (AWG#10) }	YNT-1210S	YA-4 YAT-4A YAD-4A	BCT-0514L	500	
FVD5.5-3A	 		9.5												
FVD5.5-S4A	 	4.3	8.5												
FVD5.5-4A	 		9.5												
FVD5.5-5A	 	5.3													
FVD5.5-6A	 	6.4	13.5	32.7	12.2										
B形	FVD1.25-S3B	 	3.7	7.5	17.9	5.1	9.6	4.0	0.8	赤	0.25~1.65 { 0.3 (AWG#22) 0.5 (AWG#20) 0.75 (AWG#18) 0.9 1.25 (AWG#16) }	YNT-2216	YA-1,YA-2 YAT-1A,YAT-2A YAD-1A,YAD-2A YA-4 YAT-4A YAD-4A	BCT-0514L	1,000
	FVD1.25-3B	 		8.5	22.3	7.2									
	FVD1.25-S4B	 	4.3	7.5	17.9	5.1									
	FVD1.25-4B	 		8.5	23.3	7.2									
	FVD1.25-5B	 	5.3												
	FVD1.25-6B	 	6.4	13.5	28.8	11.7									500
	FVD2-T3B	 	3.7	7.5	18.3	5.2	9.6	4.7	0.8	青	1.04~2.63 { 1.25 (AWG#16) 2.0 (AWG#14) }	YNT-1614	YA-1,YA-2 YAT-1A,YAT-2A YAD-1A,YAD-2A YA-4 YAT-4A YAD-4A	BCT-0514L	1,000
	FVD2-3B	 		8.5	21.8	7.2									
	FVD2-T4B	 	4.3	7.5	18.3	5.2									
	FVD2-4B	 		8.5	21.8	7.3									
	FVD2-5B	 	5.3												
	FVD2-6B	 	6.4	13.5	28.8	11.7									500
	FVD5.5-S3B	 	3.7	7.6	25.2	6.2	14.0	6.5	1.0	黄	2.63~6.64 { 3.5 (AWG#12) 5.5 (AWG#10) }	YNT-1210S	YA-4 YAT-4A YAD-4A	BCT-0514L	500
	FVD5.5-3B	 		8.5	26.7	7.5									
	FVD5.5-S4B	 	4.3	7.6	25.2	6.2									
	FVD5.5-4B	 		8.5	26.7	7.5									
	FVD5.5-5B	 	5.3												
	FVD5.5-6B	 	6.4	13.5	33.7	12.2									250

注1) 丸先開形端子(X形)、丸横開形端子(Y形)仕様も製作できます。詳細は弊社までお問い合わせください。

注2) 本製品の中には多少納期を要するものもあります。