



銅スリーブ付角先開形端子(ストレート形)



A形


B形




形 番		寸 法(mm)							適 用 電 線 範 囲			適 用 圧 着 工 具			1箱 入数 (個)																		
		d2	B	L	F	ℓ	φD	T	単線 (mm)	撚線(mm²)	AWG (#)	手 動	空 気 圧 式	油 圧 式																			
A形	D1.25-B3A	3.2	5.8	19.3	6.3	8.3	3.4	0.8	0.57～1.44	0.25～1.65	22～16	YDT-2216	YA-1 YA-2 YAT-1A YAT-2A YAD-1A YAD-2A YA-4 YAT-4A YAD-4A	—	1,000																		
	D1.25-YS3A	3.7	6.4	18.9																													
	D1.25-S3A		7.2	19.3																													
	D1.25-N3A		6.2																														
	D1.25-YS4A	4.3	6.4	18.9	7.0																												
	D1.25-S4A		7.2	19.3																													
	D1.25-4A	8.5																															
	D1.25-5A	5.3	9.5																														
	D1.25-6A	6.4	12.0	25.5																												11.0	
	D2-N3A	3.2	5.9	19.3		6.3	8.3	4.1	0.8	1.14～1.82	1.04～2.63	16～14	YDT-1614	YA-1 YA-2 YAT-1A YAT-2A YAD-1A YAD-2A YA-4 YAT-4A YAD-4A	—																	1,000	
	D2-YS3A	3.7	6.4	18.9																													
	D2-S3A		7.2	19.5		6.5																											
	D2-YS4A	4.3	6.4	18.9		6.3																											
	D2-YM4A		6.8			7.3																											
	D2-S4A		7.2	19.5												6.5																	
	D2-4A	8.5	20.3																														
	D2-5A	5.3	9.5																														
	D2-6A	6.4	12.0	25.5		11.0																											
	D5.5-S3A	3.7	7.2	24.7		7.5	12.0	5.7	1.0	1.82～2.89	2.63～6.64	12～10	YDT-1210S	YA-4 YAT-4A YAD-4A	—									500									
	D5.5-3A		9.5																														
	D5.5-S4A	4.3	8.5																														
	D5.5-4A		9.5																														
	D5.5-5A	5.3																															
	D5.5-6A	6.4	13.5	30.7		12.2																											
B形	D1.25-S3B	3.7	7.5	16.6		5.1	8.3	3.4	0.8	0.57～1.44	0.25～1.65	22～16	YDT-2216	YA-1,YA-2 YAT-1A,YAT-2A YAD-1A YAD-2A,YA-4 YAT-4A YAD-4A	—									1,000									
	D1.25-3B		8.5	21.0	7.2																												
	D1.25-S4B	4.3	7.5	16.6	5.1																												
	D1.25-4B		8.5	22.0	7.2																												
	D1.25-5B	5.3			500																												
	D1.25-6B	6.4	13.5	27.5		11.7																											
	D2-T3B	3.7	7.5	17.0		5.2	8.3	4.1	0.8	1.14～1.82	1.04～2.63	16～14	YDT-1614	YA-1,YA-2 YAT-1A,YAT-2A YAD-1A YAD-2A,YA-4 YAT-4A YAD-4A	—	1,000																	
	D2-3B		8.5	20.5		7.3																											
	D2-T4B	4.3	7.5	17.0		5.2																											
	D2-4B		8.5	20.5		7.3																											
	D2-5B	5.3			500																												
	D2-6B	6.4	13.5	27.5		11.7																											
	D5.5-S3B	3.7	7.6	23.2		6.2	12.0	5.7	1.0	1.82～2.89	2.63～6.64	12～10	YDT-1210S	YA-4 YAT-4A YAD-4A	—	500																	
	D5.5-3B		8.5	24.7		7.5																											
	D5.5-S4B	4.3	7.6	23.2		6.2																											
	D5.5-4B		8.5	24.7		7.5																											
	D5.5-5B	5.3			250																												
	D5.5-6B	6.4	13.5	31.7		12.2																											

注1) 丸先開形端子(X形)、丸横開形端子(Y形)仕様も製作できます。詳細は弊社までお問い合わせください。

注2) 本製品の中には多少納期を要するものもあります。




銅スリーブ付角先開形端子 (F形)



A形

B形



形 番		寸 法(mm)							適 用 電 線 範 囲			適 用 圧 着 工 具			1箱 入数 (個)	
		d2	B	L	F	ℓ	φD	T	単線(mm)	撚線(mm ²)	AWG(＃)	手 動	空 気 圧 式	油 圧 式		
A形	FD1.25-B3A	3.2	5.8	19.5	6.3	8.5	4.0	0.8	0.57～1.44	0.25～1.65	22～16	YDT-2216	YA-1 YA-2 YAT-1A YAT-2A YAD-1A YAD-2A YA-4 YAT-4A YAD-4A	—	1,000	
	FD1.25-YS3A	3.7	6.4	19.1												
	FD1.25-S3A		7.2	19.5												
	FD1.25-N3A		6.2													
	FD1.25-YS4A	4.3	6.4	19.1	7.0											
	FD1.25-S4A		7.2	19.5												
	FD1.25-4A	8.5														
	FD1.25-5A	5.3	9.5													
	FD1.25-6A	6.4	12.0	25.7	11.0											
	B形	FD2-N3A	3.2	5.9	19.5	6.3	8.5	4.7	0.8	1.14～1.82	1.04～2.63	16～14	YDT-1614	YA-1 YA-2 YAT-1A YAT-2A YAD-1A YAD-2A YA-4 YAT-4A YAD-4A	—	1,000
FD2-YS3A		3.7	6.4	19.1												
FD2-S3A			7.2	19.7												
FD2-YS4A			6.4	19.1	6.3											
FD2-YM4A		6.8	20.5			7.3										
FD2-S4A		7.2		19.7	6.5											
FD2-4A		8.5														
FD2-5A		5.3	9.5													
FD2-6A		6.4	12.0	25.7	11.0											
C形		FD5.5-S3A	3.7	7.2	26.1	7.5	13.4	6.5	1.0	1.82～2.89	2.63～6.64	12～10	YDT-1210S	YA-4 YAT-4A YAD-4A	—	500
	FD5.5-3A	9.5														
	FD5.5-S4A	4.3	8.5													
	FD5.5-4A		9.5													
	FD5.5-5A	5.3														
	FD5.5-6A	6.4	13.5	32.1	12.2											
	D形	FD1.25-S3B	3.7	7.5	16.8	5.1	8.5	4.0	0.8	0.57～1.44	0.25～1.65	22～16	YDT-2216	YA-1,YA-2 YAT-1A,YAT-2A YAD-1A YAD-2A,YA-4 YAT-4A YAD-4A	—	1,000
		FD1.25-3B		8.5	21.2	7.2										
		FD1.25-S4B	4.3	7.5	16.8	5.1										
		FD1.25-4B		8.5	22.2	7.2										
FD1.25-5B		5.3														
FD1.25-6B		6.4	13.5	27.7	11.7											
FD2-T3B		3.7	7.5	17.2	5.2	8.5	4.7	0.8	1.14～1.82	1.04～2.63	16～14	YDT-1614	YA-1,YA-2 YAT-1A,YAT-2A YAD-1A YAD-2A,YA-4 YAT-4A YAD-4A	—	1,000	
FD2-3B			8.5	20.7	7.3											
FD2-T4B		4.3	7.5	17.2	5.2											
FD2-4B			8.5	20.7	7.3											
FD2-5B	5.3															
FD2-6B	6.4	13.5	27.7	11.7												
E形	FD5.5-S3B	3.7	7.6	24.6	6.2	13.4	6.5	1.0	1.82～2.89	2.63～6.64	12～10	YDT-1210S	YA-4 YAT-4A YAD-4A	—	500	
	FD5.5-3B		8.5	26.1	7.5											
	FD5.5-S4B	4.3	7.6	24.6	6.2											
	FD5.5-4B		8.5	26.1	7.5											
	FD5.5-5B	5.3														
	FD5.5-6B	6.4	13.5	33.1	12.2											

注1) 丸先開形端子(X形)、丸横開形端子(Y形)仕様も製作できます。詳細は弊社までお問い合わせください。

注2) 本製品の中には多少納期を要するものもあります。