

INTELLIGENT TRANSMITTER WITH DIGITAL INDICATION

LEO 3

RS485-BUS-INTERFACE / SCALABLE 4...20 mA OUTPUT

LEO 3 is a micro-processor based transmitter with digital double-display for pressure (top of display) and for the analog output signal (bottom display). The display is powered from the 4...20 mA current loop.

The following functions can be executed with the front keys:

- MAX/MIN** Activating the right key brings the Max.- and Min.-values to the lower display.
- RESET** With RESET, the Max.- and Min.-values are set to actual.
- ZERO SET** The zero is set to the applied pressure.
- ZERO RES** Factory zero setting will be restored.
- UNITS** The pressure values can be displayed in the following units:
bar, mbar/hPa, kPa, MPa, PSI, kp/cm².

Programming the analog output via the front keys

- OUTP SETT** In this sub-menu the analog output can be configured within the pressure range.
- ZERO** Executing ZERO when pressure is applied sets the analog output to 4 mA.
- FS** Executing FS when pressure is applied sets the analog output to 20 mA.
- FACT SETT** The analog output signal is set back to factory settings.

Scope of delivery


Cable plug for Binder 723

Optional accessories

Protective rubber covering, K114-B interface converter

PC-Software

Pressure and temperature readings can be displayed and recorded on PC or Laptop with help of the software ControlCenterSeries30 (CCS30) and a serial interface cable. The software also enables configuration of the analog output scaling and zero point settings. The Keller-Bus protocol and programming examples in various programming languages are available. This allows very quick and easy implementation in customer software applications. Up to 128 devices can be connected together into a KELLER Bus-system.



Display segments LEO 3


SPECIFICATIONS

Pressure Ranges rel. PR	-1...3	-1...10	-1...30					bar
Pressure Ranges abs. PA		0...30	0...100	0...300	0...700	0...1000		bar
PAA	0...4	0...10	0...30					bar
Overpressure	8	20	60	200	600	1100	1100	bar
Resolution Pressure Display (LCD)	1	2	10	20	100	200	200	mbar
Resolution Pressure via Interface	0,0125 %FS							
Accuracy RT (room temperature) **	≤ 0,1 %FS							
Total Error Band (0...50 °C)	≤ 0,2 %FS							
Storage Temperature / Operating temperature	-10...60 °C / 0...50 °C							
Compensated Temperature Range *	0...50 °C							
Supply	8...28 VDC							
Output	4...20 mA (2 wire) / RS 485							
Interface	RS 485 (KELLER-Bus)							
Measuring Rate	up to 90 times/sec.							
Display Rate	2 times/sec.							
Pressure Connection *	G1/4"							
Electrical Connection *	Binder 723 (back entry)							
Protection	IP65							
Diameter x Height x Depth / Weight	76 x 125 x 50 mm / ≈ 210 g							

*Options: others Pressure Ranges, Temperature Ranges, Pressure Connections, Electrical Connections **Includes Linearity + Repeatability + Hysteresis

Pin assignment

Output	Function	Binder 723
4...20 mA (2 wire)	OUT /GND	1
	+Vcc	3
Interface	RS485A	4
	RS485B	5
⏏	Shielding	Housing



Subject to alterations

09/2013

KELLER AG für Druckmesstechnik
KELLER Ges. für Druckmesstechnik mbH

St. Gallerstrasse 119
Schwarzwaldstrasse 17

CH-8404 Winterthur
D-79798 Jestetten

Tel. +41 (0)52 - 235 25 25
Tel. +49 (0)7745 - 9214 - 0

Fax +41 (0)52 - 235 25 00
Fax +49 (0)7745 - 9214 - 60