

The Model 2020 Golight™ is designed to be a permanent mounted spotlight with a dash mounted remote, which gives the operator a full 370° horizontal rotation and a 135° vertical tilt. The Directional Flexibility of the Golight™ provides excellent light penetration with the new Cr5 Pentabeam technology.

OPERATION OF GOLIGHT™

1. Use the toggle switch on the dash control to turn the light on/off.
2. The 4-way joystick on the dash control rotates your light to the desired location.

BULB REPLACEMENT

The Golight™ utilizes a Cr5 Pentabeam bulb, which may be purchased through Golight, Inc. 308-278-3131 or 800-557-0098.

GOLIGHT™

THREE YEAR LIMITED WARRANTY

Golight™, Inc. warrants the Golight™ Model 2020 against any deemed defects that are due to workmanship for parts or faulty materials, except lamps, for three years from date of original purchase. This warranty to the Golight™ Model 2020 does not cover damage resulting from unreasonable use or misuse and unreasonable maintenance or loss.

Warranty cards must be filled out and sent within 30 days of purchase to Golight™, Inc., R. 3, Box 37B Culbertson, NE 69024, for warranty protection.

If the Golight™ Model 2020 does fail to operate under warranted specification, send the light and remote controls postage paid, plus \$9.95 for shipping and handling to Golight™, Inc., Service Department, R 3 Box 37B, Culbertson, NE 69024. No C.O.D.'s accepted. Only the above manufacturer is authorized to perform warranty repair or replace product.

Any consequential damages to person or property are excluded from this warranty. Some states do not allow the exclusion and limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific legal rights and you may also have other rights.

The Golight™ includes:

- Golight™ Model 2020 Searchlight
- Gasket for Golight™ base
- Screws and Caps
- Dash Mount remote with quick connects
- 20' 6 wire cord with positive and negative
- 12-volt wire

MOUNTING INSTRUCTIONS

1. Determine location of dash mount remote. Create an opening and insert dash mount remote with correlating quick connect on 20' cord.
2. Determine location for Golight™. (Extra 10' and 20' quick connect cords are available if needed) Create opening for Golight™ cord. Place gasket on Golight™ and attach correlating quick connect to Golight™. Set in place. Use silicone sealant to fill opening.

IMPORTANT: Allow 3" of cord to remain under the light to insure full 370° rotation.

3. The 12-volt DC power wire should be joined to the leads on the 20' cable with appropriate automotive wire attachments. It is critical that polarity be observed. The (+) lead of the Golight™ is marked with a red tag. The power should be fused at 15 Amps and be on an ignition switched circuit if possible.
4. Attach Golight™ to designated location with screws and cover with 4 white caps provided.
5. Attach Dash Mount remote to designated location with screws. Unit is installed.

IMPORTANT SAFETY INFORMATION

^This symbol is to alert you to important operating or servicing instructions that appear in your instructions. Always follow basic safety precautions when using this product to reduce the risk of injury, fire or electric shock.

^This light is for off road and utility use only. It is not designed for road use as a driving light.

^FCC RULE Part. 15.21 Changes or modifications made by the user not expressly approved by Golight™, Inc. for compliance could void the user's authority to operate the equipment.

^This light is not designed to be mounted upside down. Inverted mounting will void warranty.

For safe and efficient operation of your Golight™, observe these guidelines:

Using your Golight™ in icing conditions could damage the gear motors. (Optional dome available see accessory sheet)