


LASOS®

DPSS laser series

Directly frequency-doubled solid-state laser 10, 50 or 100 mW at 473 nm



BLK 73XX TS

- Single frequency
- Outstanding long term stability
- Excellent beam quality
- Reliable and robust
- Maintenance free
- Compact design
- Suitable for OEM applications
- Customization on request

Directly frequency-doubled solid-state laser

Specifications BLK series:

Wavelength	473 nm \pm 0.5 nm
Wavelength stability (8 h)	±0.002 nm
Spectral Linewidth ¹	< 1 MHz
Output power	10, 50 or 100 mW
Output power stability within 8 h	<±2.0 %
Noise 30 Hz 10 MHz	≤ 0.5 % rms
Warm up period	< 10 min
Transversal mode M ²	≤ 1.2
Beam waist diameter (1/e²)	0.7 mm (0.32 mm on request)
Beam ellipticity	0.91.1
Pointing stability	$<$ 6 μ rad K ⁻¹
Beam divergence	≤ 1.1 mrad
Polarization ratio	≥ 200:1
Controller	CKL 2440, CKL 2405, CKL 1005

¹Allan Deviation for sample period < 0.5 s

Options on request


Dimensions [mm]: Laser Head







Controller (CKL 2440/CKL 2405/CKL 1005)







145

LASOS® DPSS laser series

The LASOS® DPSS laser series provide excellent beam quality in a variety of wavelengths based on the latest progress in solid state laser technology.

The LASOS® DPSS laser series offers a reliable and compact single frequency laser source in the VIS.

The LASOS® DPSS laser series provide the ideal products for applications in:

- Spectroscopy
- Interferometry
- Confocal and fluorescence microscopy
- Bioanalytical research
- Particle measurements
- Metrology
- Industrial measurements
- Medical
- Science and education

Customized solutions for specific applications are possible

LASOSFor worldwide photonics

LASOS Lasertechnik GmbH Franz-Loewen-Str. 2 07745 Jena Germany

Phone: +49 (0) 3641 2944 - 0 Fax: +49 (0) 3641 2944 - 300

sales@lasos.com

www.lasos.com