

## LASOS<sup>®</sup> DPSS laser series

Directly frequency-doubled solid-state laser 5, 10 or 20 mW at 320 nm



- Single frequency
- Outstanding long term stability
- Excellent beam quality
- Reliable and robust
- Maintenance free
- Compact design
- Suitable for OEM applications
- Customization on request

## Directly frequency-doubled solid-state laser

## Specifications DLK series:

## LASOS<sup>®</sup> DPSS laser series

The LASOS® DPSS laser series provide excellent beam quality in a variety of wavelengths based on the latest progress in solid state laser technology.

The recently introduced DLK series offers a reliable and compact single frequency laser source in the UV.

The LASOS<sup>®</sup> DPSS laser series provide the ideal products for applications in:

- Spectroscopy
- Interferometry
- Confocal and fluorescence
  microscopy
- Bioanalytical research
- Particle measurements
- Metrology
- Industrial measurements
- Medical
- Science and education

Customized solutions for specific applications are possible



LASOS Lasertechnik GmbH Franz-Loewen-Str. 2 07745 Jena Germany

Phone: +49 (0) 3641 2944 - 0 Fax: +49 (0) 3641 2944 - 300 sales@lasos.com

www.lasos.com

Wavelength	319.8 nm $\pm$ 0.5 nm
Wavelength stability (8 h)	±0.002 nm
Spectral Linewidth <sup>1</sup>	< 1 MHz
Output power	5, 10 or 20 mW
Output power stability within 8 h	<±1.0 %
Noise 30 Hz 10 MHz	$\leq$ 2.0 % rms
Warm up period	< 10 min
Transversal mode M <sup>2</sup>	≤ 1.2
Beam waist diameter (1/e²)	0.7 mm (0.32 mm on request)
Beam ellipticity	0.8 1.2
Pointing stability	$<$ 6 $\mu$ rad K <sup>-1</sup>
Beam divergence	≤ 1 mrad
Polarization ratio	≥ 200:1
Controller	CKL 2405, CKL 1005
<sup>1</sup> Allan Deviation for sample period $< 0.5$ s	

Options on request

Dimensions [mm]: Laser Head

Controller (CKL 2405/CKL 1005)















