

10mm Toko 10K Equivalent

Inches/[mm]
±.010/[±.25]
2 x size

- Toko Equivalent Hardware
- Optional Capacitor Fits in Base
- Q vs Frequency Graph on Page 5
- Winding Capacity Table on Page 6
- Ferrite Tuning Core and Fixed Cup
- Quality Inspection Level: MIL-STD-1916 Level IV
- Available as: Un-wound Hardware or Complete Wound Coils

ROHS COMPLIANT REACH

L40 SERIES

Tuned Core
Fixed Cup

PHOTO NOT TO SCALE

ASSEMBLY PART NO.	COLOR CODE	MAGNETIC MATERIAL(1)	FREQUENCY RANGE(2)	MATERIAL PERMEABILITY	ASSEMBLY AL. nH/turns ² (3)	MAX μH 100 turns	MIN μH (4) 100 turns	TEMPERATURE STABILITY(5)
L40-53-BT-D-5	None	FERRITE 51	.05-20 MHz	44	16.0	160	56	1500 ppm/°C
L40-54-BT-D-5	None	FERRITE 52	2-200 MHz	25	47.0	470	137	1500 ppm/°C

1) The ferrite materials are used in the tuning core and cup core.
 2) This represents the frequency range for Q optimization in tuned or resonant circuits. The inductive properties of the material is effective over a considerably wider frequency range.
 3) Nanohenries (10⁻⁹ Henries) per turn squared.
 4) The minimum inductance is measured in microhenries (10⁻⁶ Henries) per 100 turns with the tuning core tuned out of the winding area but still a part of the assembly.
 5) The temperature stability is of the magnetic material, measured in parts per million per degree Celsius (ppm/°C) on a toroidal core and winding. This is only an indication of the temperature stability for a complete wound assembly.

Custom Wound Variable Coils

Example Part Number

Toko Style Code: L40-10K-L-2.0-7.96-BM
 Lodestone Part Code: L40-10K-C-22-10.7-A

Inductive Application: Inductance (μH), Test Freq (MHz)
 Capacitive Application: Self Resonant Freq (MHz), Capacitance (pf)

Winding Style: A, EK,N,N2, Z, HM, BHD, M, L, YUK

Test Frequencies (Mhz): 25.2 (0.1 to 1μH), 7.96 (1μH to 10μH), 2.52 (10 to 100μH), .796 (100μH to 1mH), .252 (1mH to 10mH)

Internal Capacitors (pf): Selected to meet the specified self-resonant frequency

Inductance Range

Frequency Range

Custom Variable Coils are wound to your Inductance and Frequency Specifications, or with Capacitors to your Self-resonant Frequency Specifications.

Assembly Sub-components

Actual Size

5 TERMINAL ASSEMBLY	BASE with COIL FORM (6)	COLOR CODE	DRUM CORE (8)	CUP CORE	SHIELD CAN
L40-53-BT-D-5	B340	None	TH25-353	C12-6053	CN340BT
L40-54-BT-D-5	B340	None	TH25-354	C12-6054	CN340BT

6) "The base is molded in a phenolic thermoset. The attached coilform is molded in polypropylene. The 5 terminals are brass, .027 inches (0.7mm) in diameter, 100% tin plated to meet MIL-STD 202 method 208 for solderability."
 7) The base has a cavity for an optional capacitor. .225 [5.7mm] Long x .062 [1.6mm] Wide x .107 [2.7mm] Deep. Capacitors are not included.