

LODESTONE PACIFIC



Phone: (800) 694-8089
 www.lodestonepacific.com
 E-mail: sales@lodestonepacific.com

+/- .010 Inches (mm), 2 x Size

STM198-06

Material: LCP (Natural)
UL Rating: UL94-VO, Class F
6 Terminals: Self Terminating
Packaging Method: Bulk in Poly Bags
 See RoHS compliant PVC packaging trays options on page 57.
Application: For surface mounting of toroids with wound diameters up to .221 inches and a max height of .056 inches. The toroid leads are tinned, and wrapped around the tabs on the toroid mount. The toroid leads then make direct contact to the PCB during infrared solder reflow.

Made in our China Factory

Request samples and literature and have them ship to you same day.
www.lodestonepacific.com/samplepricing.php

View daily updated inventory levels in USA and Hong Kong warehouses.
www.lodestonepacific.com/search.php

Request a quote and delivery and have it e-mailed to you same day.
www.lodestonepacific.com/quote.php

Search for a part to match your applications, download the .pdf
www.lodestonepacific.com/selectoroid.php

Search for REACH documents, view or download the certifications .pdf.
www.lodestonepacific.com/reach.php

Search our Coil Winder Data Base, for capabilities to match your specs.
www.lodestonepacific.com/coilwinders.php