



MA-WC36-DP15

3.3-4.01 GHz Dual Polarization Base Station Antenna, 60°

MARS 60° Broadband Dual Polarized Sector Antenna provides a cost effective solution for LTE & WiMAX applications. Additional Features:

- Stable performance with 15dBi of gain.
- Compact size allowing for easy blending with any environment.
- Tilt mount allowing quick and easy installation.
- UV protected radome suitable for harsh environment installations.



Specifications

Electrical	
Frequency range	3.3-4.01 GHz
GAIN, typ.	15 dBi
VSWR, max.	1.7 : 1
Polarization	Linear, Vertical & Horizontal
3 dB Beam-Width, Az-Plane, typ.	60°
3 dB Beam-Width, El-Plane, typ.	12°
Side Lobes, typ.	-12 dB
Cross Polarization, min.	-15 dB
Port to Port Isolation, min.	-30 dB
Front to Back Ratio, min.	-35 dB
Input power, max.	10 Watt
Input Impedance	50 Ohm
Lightning Protection	DC Grounded
Mechanical	
Dimensions (HxWxD)	370 x 370 x 40 mm (14.5" x14.5" x1.6")
Connector	2 x N-Type, Female
Weight	2 Kg.
Back Plane	Aluminum; protected through chemical passivation
Radome	UV Protected Polycarbonate
Mounting	See Ordering Options
Environmental	
Operating Temperature Range	-55°C to +65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 Km/h (Survival)
Flammability	UL94
Water Proofing	IP-65
Humidity	ETS 300 019-1-4,EN 302 085 (Annex A.1.1)
Salt Fog	According to IEC 68-2-11
Ice and Snow	25mm radial (survival)

Ordering Options	
MA-WC36-DP15	Antenna Suited for MNT-22 (optional wall/pole adjustable mount)
MA-WC36-DP15B	Antenna with MNT-22 mount

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.