



MA-WD36-DP14N

3.3-4.01 GHz Dual Polarized Base Station Antenna, 90°

MARS 90° Broadband Dual Polarized Sector Antenna provides a cost effective solution for LTE & WiMAX applications. Additional Features:

- Stable performance with 14 dBi of gain.
- Compact size allowing for easy blending with any environment.
- Tilt mount allowing quick and easy installation.
- UV protected radome suitable for harsh environment installations.



Specifications

_		-	-	
FI	6	ct	rı	cal

Frequency range	3.3-4.01 GHz
GAIN, typ.	14 dBi
VSWR, max.	1.7 : 1
Polarization	Dual, Vertical & Horizontal
3 dB Beam-Width, Azimuth, typ.	90°
3 dB Beam-Width, Elevation, typ.	12°
Side Lobes, min.	-12 dB
Front to Back Ratio, min.	-30 dB
Cross Polarization, min.	-15 dB
Port to Port Isolation, typ.	-30 dB
Input power, max.	10 Watt
Input Impedance	50 Ohm
Lightning Protection	DC Grounded

Mechanical

370 x 370 x 40 mm (14.5" x 14.5" x 1.6")
2 Kg.
2 x N-Type, Female
Aluminum protected through chemical passivation
UV Protected Polycarbonate
See ordering options

Environmental

Operating Temperature Range	-55°C to +65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 km/h (survival)
Flammability	UL94
Water Proofing	IP-67
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)
Salt Fog	According to IEC 68-2-11
Ice and Snow	25mm radial (survival)

	 na			a -		
	na		127	* 1	$\boldsymbol{\cap}$	ne
4 B T		u	4 .	LI	u	113

MA-WD36-DP14N	Antenna Suited for MNT-22 (optional wall/pole adjustable mount)
MA-WD36-DP14NB	Antenna with MNT-22 mount

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.