



MA-WD90-6X

915 MHz Base Station Antenna, 90°

MARS 915 MHz Base Station Antenna provides a robust and efficient solution for the Point-to-Multi-point systems based on the ISM 915 MHz band. Additional Features:

- 90° azimuthal coverage.
- Suitable for harsh environment installations.
- · DC grounded.
- Easy mounting allowing obtaining required down tilt degree with the optional MNT-25 mount.



Specifications

| Electrical Programme Control of the | | |
|---|------------------|--|
| Frequency range | 902-928 MHz | |
| GAIN, min. | 13 dBi | |
| VSWR, max. | 1.7 : 1 | |
| Polarization | Linear, Vertical | |
| 3 dB Beam-Width, Horizontal Plane, typ. | 90° | |
| 3 dB Beam-Width, Elevation Plane, typ. | 15° | |
| Side Lobes, min. | -11 dB | |
| Cross Polarization, min. | -13 dB | |
| Front to Back Ratio, min. | -23 dB | |
| Input power, max. | 50 Watt | |
| Input Impedance | 50 Ohm | |
| Lightning Protection | DC Grounded | |

| | nical |
|--|-------|
| | |

| Dimensions (HxWxD) | 1200 x 330 x 105 mm (47.2" x 13" x 4.1") | |
|--------------------|--|--|
| Weight | 4.5 kg. | |
| Connector | N-Type, Female | |
| Back Plane | Aluminum; protected through chemical passivation | |
| Radome | UV Protected Plastic | |
| Mount | See ordering options | |

Environmental

| Operating Temperature Range | -40°C to +65°C |
|-----------------------------|---|
| Vibration | According to IEC 60721-3-4 |
| Wind Load | 200 km/h (survival) |
| Flammability | UL94 |
| Water Proofing | IP-65 |
| Humidity | ETS 300 019-1-4, EN 302 085 (annex A.1.1) |
| Salt Fog | According to IEC 68-2-11 |
| Ice and Snow | 25mm radial (survival) |

| | | _ | н- | |
|---|------|---|-------|----|
| 11. | | | - | ne |
| ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,, | ing | | ш | |
| | | | _ | |
| | | | | |

| MA-WD90-6X | Antenna Suited for MNT-25 (optional tilt mount) |
|-------------|---|
| MA-WD90-6XB | Antenna with MNT-25 mount |

Patterns are available on our website

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.