

MA-WA58-1X

5 GHz Broadband Subscriber Antenna

MARS 5 GHz Broadband High Gain Antenna covers the full 5 GHz spectrum, from lower to higher UNII band, including its unlicensed part.

Additional Features:

- Exceptionally high gain of 23 dBi over the entire frequency band.
- Diamond shape provides the highest range of ETSI standards, up to TS5.
- Light weight and durable construction.
- DC grounded for lightning protection to meet local electrical building codes.

The MARS 5GHz Antenna & Enclosure Solution comprises of Waterproof 5 GHz Broadband Antenna and Weatherproof Enclosure with provisions for Az/EI Mounting device. This solution enables WISP/Integrator to design his own low cost, weatherized subscriber unit, saving high costs of special antenna-radio integration.



Specifications

Electrical

Frequency range	4.9-5.875 GHz	
GAIN, typ.	23 dBi @ 5.15-5.875	21 dBi @ 4.9-5.15
VSWR, max.	1.5 : 1 @ 5.15-5.875	1.9 : 1 @ 4.9-5.15
Polarization	Linear, Vertical	
3 dB Beam-Width, H-Plane, typ.	10.5°	
3 dB Beam-Width, E-Plane, typ.	10.5°	
Side Lobes, min.	-23 dB	
Cross Polarization, min.	-24 dB	
Front to Back Ratio, min.	-30 dB	
Input power, max.	30 Watt	
Input Impedance	50 Ohm	
Lightning Protection	DC Grounded	

Mechanical

Dimensions (HxWxD)	305 x 305 x 15 mm (12" x 12" x 0.6")
Weight	840 gr.
Connector (without enclosure)	N-Type, Female
Connector (with enclosure)	SMA Female
Back Plane	Aluminum; protected through chemical passivation
Radome	UV Protected Polycarbonate
Enclosure - Small	171 x 167 x 68 mm. (External dimension)
Enclosure - Large	287 x 287 x 68 mm. (External dimension)
Mount	See Ordering Options

Environmental

Operating Temperature Range	-40°C to +65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 km/h (survival)
Flammability	UL94
Water Proofing	IP-67
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)
Salt Fog	According to IEC 68-2-11
Ice and Snow	25mm radial (survival)

Standard Compliance

4.9-5.15 GHz ETSI EN 302 085 V1.2.3 - TS1, TS2, TS3
5.15-5.875 GHz ETSI EN 302 085 V1.2.3 - TS1, TS2, TS3, TS4, TS5

Ordering Options

MA-WA58-1X PM	Antenna with N-Type Female connector with integral Pole Mount includes stainless steel brackets
MA-WA58-1X MNT	Antenna with N-Type Female connector Suited for MNT-22 (optional wall/pole adjustable mount)
MA-WA58-1XMNTB	Antenna with N-Type Female connector with MNT-22 mount
MA-WA58-1XSMEZY	Antenna with small enclosure, SMA Connector and MNT-22
MA-WA58-1XSMEZS	Antenna with small enclosure, SMA Connector with PEMs and MNT-22
MA-WA58-1XSMEZY	Antenna with large enclosure, SMA Connector and MNT-22
MA-WA58-1XSMEZLZ	Antenna with large enclosure, SMA Connector with PEMs and MNT-22

Patterns are available on our website

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com