



MA-WA36-DP21

3.3-3.8 GHz Dual Polarization/ Dual Slant Subscriber Antenna

MARS Broadband Dual Polarized Subscriber Antenna provides a cost effective solution for LTE & WiMAX applications. Additional Features:

- Dual slant if mounted diagonally.
- Stable performance with 22 dBi of gain.
- Compact size allowing easy blending with any environment.
- Mount allowing quick and easy 45deg. turn installation.
- UV protected radome suitable for harsh environment installations.



Specifications

Lightning Protection

Electrical		
Frequency range	3.3-3.8 GHz	
GAIN: H-Port & V-Port	22 dBi	
VSWR, max.	1.7 : 1	
Polarization Dual Pole	Linear, Vertical & Horizontal	
Dual Slant (opt.)	±45°	
3 dB Beam-Width, H-Plane, typ.	12°	
3 dB Beam-Width, E-Plane, typ.	12°	
Cross Polarization, max	ETSI TS3	
Front to Back Ratio, max.	ETSI TS3	
Side Lobes, min.	ETSI TS3	
Port to Port Isolation, typ.	-35 dB	
Input power, max.	10 Watt	
Input Impedance	50 Ohm	

Electrical

Mechanical

DC Grounded

ricchanical		
Dimensions (HxWxD)	370 x 370 x 40 mm (14.5" x 14.5" x 1.6")	
Weight	2.1 kg.	
Connector	See ordering options	
Back Plane	Aluminum; protected through chemical passivation	
Radome	UV Protected Polycarbonate	
Mount	See ordering options	

Environmental

Operating Temperature Range	-55°C to +65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 km/h (survival)
Flammability	UL94
Water Proofing	IP-67
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)
Salt Fog	According to IEC 68-2-11

Ordering Options	
MA-WA36-DP21	Antenna with 2xSMA, Female Connector Suited for MNT-22
MA-WA36-DP21B	Antenna with 2xSMA, Female Connector and MNT-22 mount
MA-WA36-DP21N	Antenna with 2xN-Type, Female Connector suited for MNT-22

Patterns are available on our website

MA-WA36-DP21NB

MARS Antennas & RF Systems proprietary information

Antenna with 2xN-Type, Female Connector and MNT-22 mount

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.