

MA-WC2458-10

2.4-2.5 & 5.15-5.875 GHz Dual Band Antenna 60°

Mars Dual Band Wi-Fi Small Factor High Gain Antenna

- Perfect for Wi-Fi Hotspots
- Exceptionally efficient performance
- High Gain /Size Ratio
- Aesthetic design
- Weatherized and durable



Specifications

Electrical

Frequency range	2.4-2.5 & 5.15-5.875 GHz
Gain, range	10dBi @ 2.4-2.5 GHz ; 11dBi @ 5.15-5.875 GHz
VSWR, max.	2 : 1
Polarization	Linear Vertical or Horizontal
3dB Beam-Width, H-Plane, typ.	60°
3dB Beam-Width, E-Plane, typ.	60°@ 2.4-2.5 GHz ; 40°@5.15-5.875 GHz
Front to Back Ratio, min.	-30 dB
Input power, max.	50 Watt
Input Impedance	50 Ohm

Mechanical

Dimensions (HxWxD)	112 x 112 x 33.5 mm (4.41" x 4.41" x 1.32")
Connector	2 x N-Type ,Female
Weight	147 gr.
Mounting	See Ordering Options
Radome	UV Protected Polycarbonate
Back Plane	Aluminum protected through chemical passivation.

Environmental

Operating Temperature Range	-40°C to +65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 Km/h (Survival)
Flammability	UL94
Water Proofing	IP-67
Humidity	ETS 300 019-1-4,EN 302 085 (Annex A.1.1)
Salt Fog	According to IEC 68-2-11

Ordering Options

MA-WC2458-10	Suited for MNT-4LU mount
MA-WC2458-10B	With MNT-4LU mount

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com