



MA-VM1765-5

1.7-6.5 GHz Wide Band Blade Antenna for Mobile Applications

MARS Wide Band Blade Antenna is a ruggedized and aerodynamic antenna that provides an optimal solution for use in mobile applications such as trains, helicopters, buses or cars.

Additional Features:

- Bottom Mount, Fixed Mount (4 screws from bottom)
- Stable and reliable performance.



Specifications

Electrical				
Frequency range	1.7-2.3 GHz	2.3-3.0 GHz	3.0-4.0 GHz	4.0-6.5 GHz
GAIN, typ.	3 dBi	4 dBi	5 dBi	6 dBi
VSWR, max.	2 : 1 max. 1.5 :1 typ.			
Polarization	Linear, Vertical			
Pattern	Omni Directional			
Input power, max	5 Watt			
Input Impedance	50 Ohm			
Mechanical				
Dimensions (LxWxH)	132 x 79 x 76 mm			
Weight	150 gr.			
Connector	N-Type Female Bottom			
Back Plane	Aluminum, protected through chemical passivation			
Radome	UV Protected Polycarbonate			
Mount	Bottom Mount, Fixed Mount (4 screws from bottom)			
Environmental				
Operating Temp. Range	-40°C to +65°C			
Vibration	According to IEC 60721-3-4			
Water Proofing	IP-67			
Flammability	UL94			
Humidity	ETS 300 019-1-4, EN 302 085 (Annex A.1.1)			

Patterns are available on our website.

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.