



## **MA-WA14-1X**

## 1425-1525 MHz Broadband Directional Antenna

MARS 1425-1525 MHz Antenna provides a cost effective and reliable solution for Fixed Wireless Data & Telephony Services and any other application in this band.

This panel antenna replaces Yagis previously used for the same purpose. Additional Features:

- Durable construction and light weight.
- Optionally available with Pole Mount or MNT-22 (pole/wall, azimuth and elevation adjustable mount).
- DC Grounded.

## **Specifications**

Electrical							
Frequency range	1425-1525 MHz						
GAIN, min.	13.5 dBi						
VSWR, max.	1.5 : 1						
Polarization	Linear, Vertical						
3 dB Beam-Width, H-Plane, typ.	31°						
3 dB Beam-Width, E-Plane, typ.	31°						
Side Lobes, min.	-13 dB						
Cross Polarization, min.	-20 dB						
Front to Back Ratio, min.	-20 dB						
Input power, max.	30 Watt						
Input Impedance	50 Ohm						
Lightning Protection	DC Grounded						
Mechanical							
Dimensions (HxWxD)	305 x 305 x 25 mm (12" x 12" x 1")						
Weight	1.2 kg.						
Connector	N-Type, Female						
Back Plane	Aluminum; protected through chemical passivation						
Radome	UV Protected Polycarbonate						
Mount	See Ordering Options						
Environmental							
Operating Temperature Range	-40°C to +65°C						
Vibration	According to IEC 60721-3-4						
Wind Load	200 km/h (survival)						
Flammability	UL94						
Water Proofing	IP-65						
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)						
Salt Fog	According to IEC 68-2-11						
Ice and Snow	25mm radial						

Ordering Options	
MA-WA14-1X PM	Antenna with integral Pole Mount includes stainless steel brackets
MA-WA14-1X MNT	Antenna Suited for MNT-22 (optional wall/pole adjustable mount)
MA-WA14-1X MNTB	Antenna with MNT-22 mount

## Patterns are available on our website

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

Tel: +972-3-5599661	•	Fax: +972-3-5599677	•	e-mail: mars@marsant.co.il	٠	web: www.mars-antennas.com		

