

MA-CM36-15

Multi Band Omni Antenna

MARS Multi Band Omni Antenna covers all the bands for 2G, 2.5G and 3G cellular, as well as ISM, WLAN and Bluetooth.

The antenna is aesthetic, small and has unobtrusive profile that blends easily with any environment.

The antenna is easy-installed and is highly recommended as an outstanding logistic solution for In-Building Installations.



Specifications

Electrical

Standard	SMR, AMPS, CDMA, TDMA, GSM 900	PCS, DECT, GSM 1900, UMTS	Bluetooth, ISM, WLAN
Frequency range	806-960 MHz	1.71-2.17 GHz	2.3-2.7 GHz
GAIN, typ.	2 dBi	3-4 dBi	5 dBi
VSWR, max.	2 : 1	1.5 : 1	1.6 : 1
Polarization	Linear, Vertical		
Input power, max.	50 Watt		
Input Impedance	50 Ohm		
Lightning Protection	DC Grounded		

Mechanical

Dimensions (HxWxD)	Base Diameter - 205 mm, Height - 89 mm
Weight	220 gr.
Connector	N-Type, Female
Back Plane	Aluminum; protected through chemical passivation
Radome	UV Protected Polycarbonate
Mount	Ceiling Mounting

Environmental

Operating Temperature Range	-40°C to +65°C
Vibration	According to IEC 60721-3-4
Flammability	UL94
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)

Ordering Options

MA-CM36-15	Antenna Indoor
MA-CM36-15R	Antenna Outdoor
MA-CM36-15T	Antenna Indoor with DC Return Option

Patterns are available on our website

Patent Pending

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com