



MA-WA55-TPMIMO

5.125-6.1 GHz Triple Polarization MIMO Subscriber Antenna

MARS Triple Polarization antenna provides coverage of 5.125-6.1 GHz frequency band in a single antenna radome.

Additional Features:

- 3 Ports: Dual Slant (±45°) and Vertical Polarization.
- Specially designed for MIMO applications for optimal decorrelation.
- Light weight and durable construction.
- UV protected radome made of polycarbonate.
- Can be customized with customer defined back plane and different connector configurations.

Specifications

| Electrical | |
|---------------------------------|---|
| Frequency range | 5.125-6.1 GHz |
| Vertical Pol. | 19 dBi |
| GAIN Dual Slant Pol. | 17.5 dBi |
| VSWR, max. | 1.7 : 1 |
| Polarization | Dual Slant ± 45° and Vertical |
| 3 dB Beam-Width-Azimuth, typ. | Dual Slant: 20°; V- Pol 22° |
| 3 dB Beam-Width-Elevation, typ. | Dual Slant: 19°; V- Pol 14° |
| Side Lobes, min. | -12 dB |
| Front to Back Ratio, min. | -35 dB |
| Port to Port Isolation | -40 dB (Vertical to ±45° Dual Slant) |
| Port to Port Isolation | -30 dB (+45° Dual Slant to -45° Dual Slant) |
| Input power, max. | 10 Watt |
| Input Impedance | 50 Ohm |
| Lightning Protection | DC Grounded |
| Mechanical | |
| Dimensions (HxWxD) | 305 x 305 x 15 mm (12" x 12" x 0.6") |
| Connector | 3 x N-Type Female |
| Weight | 1.5 kg. |
| Mounting | See ordering options |
| Radome | UV Protected Polycarbonate |
| Back Plane | Aluminum protected through chemical passivation |
| Environmental | |
| Operating Temperature Range | -55°C to +65°C |
| Vibration | According to IEC 60721-3-4 |
| Wind Load | 200 Km/h (Survival) |
| Flammability | UL94 |
| Water Proofing | IP-67 |
| Humidity | ETS 300 019-1-4,EN 302 085 (Annex A.1.1) |
| Salt Fog | According to IEC 68-2-11 |

| Ordering Options | |
|------------------|---|
| MA-WA55-TPMIMO | Antenna Suited for MNT-22 (optional wall/pole adjustable mount) |
| MA-WA55-TPMIMOB | Antenna with MNT-22 mount |

Patterns are available on our website

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

