

MR-UMTS70-20F

UMTS Bi-Directional Amplifier (WCDMA)

MR-UMTS70-20F is a full band UMTS linear repeater at low power consumption. It provides a cost effective answer for enhancing radio communication in buildings, basements, parking garages and other RF shielded environments.

Additional Features

- Auto Setup.
- Overload & Oscillation protection.
- "Down Link" RF Power indication.



Specifications

Electrical

	Down Link	Up Link
Frequency Band	2110-2170 MHz	1920-1980 MHz
Pass Band - nominal	60 MHz	
Gain at min. attenuation, min.	70 dB	
Pass Band Ripple	± 3 dB	
Maximum Output Power	20 dBm	
Range of ALC output power setting points, dBm	20-6 dBm (up to 8 set points)	
Range of AGC, dB	30 dB	
Output IP3, min.	40 dBm	
Output Power @ 1 dB Compression	30 dBm	
Noise Figure at min. attenuation, max.	5 dB	
Impedance	50 Ohm	
VSWR, max.	2 : 1	
Protection from Oscillation and Overload	Automatic	
Biassing (220 VAC/DC Adapter included)	6.7 VDC @ 2.5A max	

Mechanical

Dimensions	280 x 250 x 65 mm
Weight	2.5 kg.
Connectors	N-Type, Female
Mount	Wall / Ceiling Mounting

Environmental

Operating Temperature Range	-10°C to +50°C
Humidity, min.	95%
Splash, Dust	Protected

Mars Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 58861, P.O.Box 5 AZOR 58008, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com