



MR-DBHSDG-70YY

GSM Dual Band (900MHz & 1800MHz) Repeater

MR- DBHSDG-70YY is a high selective dual band medium RF power repeater with full band frequency range.

It provides a cost effective answer for enhancing radio communication in buildings, basements, parking garages and other RF shielded environments. Additional Features

- Auto Setup
- Oscillation & Overload Protection
- AGC



Specifications

Electrical Plants and the second seco					
	GSM 900		DCS 1800		
	Down Link	Up Link	Down Link	Up Link	
Frequency Band*	935-960 MHz	890-915 MHz	1805-1880 MHz	1710-1785 MHz	
Gain at min. attenuation	70 dB		70 dB		
Pass Band Ripple	±2 dB		±4 dB		
Max Output Power	15 dBm	15 dBm	18 dBm	18 dBm	
Output IP3, min.	36 dBm	36 dBm	40 dBm	40 dBm	
Intermodulation products, not more	-45 dBc		-45 dBc		
Limited Output Power (Shut down level)	20 dBm		23 dBm		
Range of AGC	30 dB		30 dB		
Noise Figure at min. attenuation, max.	6 dB		6 dB		
Propagation delay, max.	5 usec		5 usec		
Protection from Oscillation and Overload	Automatic		Automatic		
Impedance	50 Ohm		50 Ohm		
VSWR In/Out, max.	2:1		2:1		
Indications -Leds	"Power ON", "850 Signal", "2000 Signal"				
Standard: 3GPP TS 25.106	Compliance				
Biasing (220 VAC/DC Adapter included)	12 VDC @ 2 A				
Machanical					

Mechanical		
Dimensions	310 x 200 x 60 mm	
Weight	3 kg.	
Connectors	N-Type, Female	
Mount	Wall/Ceiling Mount	
_ , , ,		

Environmental		
Operating Temperature Range	-10°C to +50°C	
Humidity, min.	95%	
Splash, Dust	Protected	

(*) Other available on request

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.