



## **MA-WC25-DS16**

# 2.3-2.7 GHz Dual Slant Base Station Antenna, 65°

MARS Dual Slant ±45 degrees 65° sector antenna features:

- Efficient and stable performance with 2 X16 dBi of gain.
- Full 2.3-2.7 GHz band coverage.
- · High Isolation ratio.
- · Compact size.
- Optional Azimuth & Elevation Adjustable mount.

UV protected radome suitable for harsh environment installations.

Can be customized per customer requirements



### **Specifications**

ect	

Frequency range	2.3-2.7 GHz
GAIN, typ.	2 x 16dBi
VSWR, max.	1.7:1
Polarization	Dual Slant ±45°
4 dB Beam-Width, Azimuth, typ.	65°
3 dB Beam-Width, Elevation, typ.	90
Side Lobe level ( Elevation),typ.	-12 dB
Port to Port Isolation, typ.	-20 dB
Front to Back Ratio, min.	-30 dB
Input power, max.	20 Watt
Input Impedance	50 Ohm
Lightning Protection	DC Grounded

#### Mechanical

Dimensions (HxWxD)	800 x 225 x 67 mm (31.3" x 8.8" x 2.6")	
Weight	2.5 kg.	
Connector	2 x N-Type, Female	
Back Plane	Aluminum; protected through chemical passivation	
Radome	UV Protected, Plastic	
Mount	See Ordering Options	

### Environmental

Operating Temperature Range	-55°C to +65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 km/h (survival)
Flammability	UL94
Water Proofing	IP-65
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)
Salt Fog	According to IEC 68-2-11
Ice and Snow	25mm radial (survival)

Ordering Options		
144 14/00= DO40	_	

MA-WC25-DS16	Antenna 2 x N-Type Female connectors Suited for MNT-5A mount
MA-WC25-DS16B	Antenna 2 x N-Type Female connectors with MNT-5A mount

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.