



MA-WC36-2V15

3.3-4.01 GHz 2 x Vertical Polarization Base Station Antenna, 60°

MARS 60° Broadband Dual Vertical Sector Antenna provides a cost effective solution for LTE & WiMAX applications.

Additional Features:

- Stable performance with 15dBi of gain.
- Compact size allowing for easy blending with any environment.
- Tilt mount allowing quick and easy installation.
- UV protected radome suitable for harsh environment installations.



Specifications

_	•		-		
	0	ct	rı	ca	7
LI	_			La	u

Frequency range	3.3-4.01 GHz
GAIN, typ.	15 dBi
VSWR, max.	1.7 : 1
Polarization	2 x Vertical
3 dB Beam-Width, Az-Plane, typ.	60°
3 dB Beam-Width, El-Plane, typ.	12°
Side Lobes, typ.	-12 dB
Cross Polarization, min.	-15 dB
Port to Port Isolation, min.	-30 dB
Front to Back Ratio, min.	-35 dB
Input power, max.	10 Watt
Input Impedance	50 Ohm
Lightning Protection	DC Grounded

Mechanical

Dimensions (HxWxD)	370 x 370 x 40 mm (14.5" x14.5" x1.6")
Connector	2 x N-Type, Female
Weight	2 Kg.
Back Plane	Aluminum; protected through chemical passivation
Radome	UV Protected Polycarbonate
Mounting	See Ordering Options

Environmental

-55°C to +65°C
According to IEC 60721-3-4
200 Km/h (Survival)
UL94
IP-65
ETS 300 019-1-4,EN 302 085 (Annex A.1.1)
According to IEC 68-2-11
25mm radial (survival)

Ordering Options	
NAA 14/000 01/45	A - t O - 't - I (MANIT - OO / t' I II/ I I' t - I

MA-WC36-2V15 Antenna Suited for MNT-22 (optional wall/pole adjustable mount)
MA-WC36-2V15B Antenna with MNT-22 mount

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.