



MA-WC25-DP14

2.3-2.7 GHz Dual Polarized Base Station Antenna, 60°

MARS 60° Base Station Antenna with 14 dBi of gain is light-weight yet has a robust and durable construction.

Antenna Features:

- · Quick and easy installation.
- Small, aesthetic and unobtrusive radome.
- Easily adapted to any RF connector.
- Easy mounting allows obtaining required down tilt degree.

Applications:

- · Point-to-Multi-Point Systems.
- WLL applications.
- MMDS.
- ISM applications.



Specifications

e	ec	ect	ectri	ectric	ectrica

Frequency range	2.3-2.7 GHz
GAIN, typ.	14 dBi
VSWR, max.	1.7 : 1
Polarization, Dual Pole	Linear, Vertical & Horizontal
3 dB Beam-Width, Az-Plane, typ.	60°
3 dB Beam-Width, El-Plane, typ.	16°
Side Lobes, min.	-12 dB
Cross Polarization, min.	-15 dB
Port to Port Isolation, min.	-35 dB
Front to Back Ratio, min.	-25 dB
Input power, max.	10 Watt
Input Impedance	50 Ohm
Lightning Protection	DC Grounded

Mechanical

Dimensions (HxWxD)	370 x 370 x 40 mm (14.5" x 14.5" x 1.6")
Connector	2 x N-Type, Female
Weight	1.8 Kg.
Back Plane	Aluminum; protected through chemical passivation
Radome	UV Protected Polycarbonate
Mounting	See ordering options

Environmental

-55°C to +65°C
According to IEC 60721-3-4
200 Km/h (Survival)
UL94
IP-67
ETS 300 019-1-4,EN 302 085 (Annex A.1.1)
According to IEC 68-2-11

Ordering Options	
MA-WC25-DP14	Antenna Suited for MNT-22 (optional wall/pole adjustable mount)
MA-WC25-DP14B	Antenna with MNT-22 mount

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.